

EC-TYPE EXAMINATION CERTIFICATE

Application of: Council Directive 96/98/EC of 20 December 1996 on Marine Equipment as amended by directive 2014/93/EU, issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Directorate. This Certificate is issued by DNV GL AS under the authority of the Government of the Kingdom of Norway.

This is to certify:**That the Lifeboats**

with type designation(s)
NPT67FF/FC Free Fall Life Boat

Issued to


Jiangyin Neptune Marine Appliance Co., Ltd.
Jiangyin City, China

is found to comply with the requirements in the following Regulations/Standards:

Annex A.1, item No. A.1/1.17 and Annex B, Module B in the Directive. SOLAS 1974 as amended, Reg. III/4, III/21, III/31, III/34 & X/3, LSA Code and 2000 HSC code 8.

Further details of the equipment and conditions for certification are given overleaf.

Høvik, 2015-10-29
for **DNV GL AS**



This Certificate is valid until
2020-10-27

Notified Body No.: **0575**

Vidar Dolonen
Head of Department

DNV GL local office:
Jiangyin FiS&CMC

Piotr Orzechowski
Surveyor

Job Id: **344.1-001545-16**
Certificate No: **MEDB00000BJ**

Product description

"NPT67FF/FC Free Fall Life Boat"

Totally enclosed free-fall lifeboat fire-protected and with self-contained air support system.

Length:	6.70 m
Breadth:	2.55 m
Depth:	0.90 m
Weight of boat, fully equipped:	4000 kg
Weight of boat, fully manned (82.5 kg per person):	6475 kg

Hook manufacturer and type:	Jiangyin Neptune Marina Appliance Co Ltd, NPT70HKF, onload
Hook SWL	7000 kg
Hull material:	GRP

Propulsion system:	Inboard engine
Engine manufacturer and type:	Zhenjiang Siyang Diesel, 380J-3 Changzhou Bosin Mechanical, BS380J Aabenraa Motorfabrik, BUKH DV29RME Sabb Motor A.S., Sabb L3.139LB Yanmar Diesel Engine Co.Ltd, Yanmar 3JH30A

Bollard pull:	3.9 kN for 380J-3 3.8 kN for BS380J 4.0 kN for DV29RME 3.2 kN for L3.139LB 3.9 kN for 3JH30A
---------------	--

Application/Limitation

Approved engine power:	20.6 kW for 380J-3 22.6 kW for BS380J 21.3 kW for DV29RME 21.6 kW for L3.139LB 22.1 kW for 3JH30A
------------------------	---

Maximum number of persons (82.5 kg per person):	30
Maximum load of persons (82.5 kg per person):	2475 kg

Maximum free-fall certification height	20.0 m
Minimum launching ramp length	7.50 m
Launching ramp angle	35°

- Unless free-fall lifeboat lashing can be released from inside it shall be arranged to preclude boarding until it is removed.
- For free-fall lifeboats inflatable lifejackets are recommended.
- Lifeboat equipment and marking/instructions to be inspected after installation onboard the ship.
- Equipment shall comply with LSA Code and IMO Res.MSC.81(70).
- The design assessment is based on IMO Res. MSC 48(66) as amended by IMO Res. MSC 207(81), IMO Res. MSC 218(82) and IMO Res. MSC 272(85).
- Production and installation testing shall be carried out according to IMO Res. MSC. 81(70), part 2.

Job Id: **344.1-001545-16**
Certificate No: **MEDB00000BJ**

Type Examination documentation

Basis for approval:

Drawings (as applicable)	2010-10-22
Prototype test report witnessed by DNV	2010-09-(14-15)
Material test report	2010-09-29
Test report of Fire-retardant material (IMO MSC. /Circ. 1006), Shanghai R&D Centre of Polymer material, Shanghai, China	2009-08-12

Tests carried out

Tests are documented in accordance with recommendation on testing of Lifesaving Appliances, IMO Res. MSC 81(70) part 1, as amended by IMO Res. MSC.226(82) & IMO Res. MSC.274(85), IMO Res. MSC.323(89) and IMO MSC./Circ.1006.

Marking of product

The product is to be indelibly marked with name of manufacture, type designation, dimensions and date of manufacture, according to LSA code item 4.4.1.2.

Mark of Conformity

The manufacturer is allowed to affix the Mark of Conformity according to Article 11 in the Council Directive 96/98/EC on Marine Equipment and shall issue a Declaration of Conformity, only when the module D or E or F of Annex B in the same directive is fully complied with.

Module D: The quality system for production and testing shall be approved by the Notified Body.

Module F: Compliance of the products to type as described in this EC Type-Examination Certificate must be verified by the Notified Body who also shall issue a Certificate of Conformity.