DNV·GL

Certificate No:
MEDB00001SA

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of the Kingdom of Norway.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: paint systems

with type designation(s)
JOTACOTE F60

Issued to
Jotun A/S
SANDEFJORD, Norway

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2015/559,**
Annex A.1, item No. A.1/3.18b and Annex B, Module B in the Directive; SOLAS 74, Reg. II-2/3, II-2/5, II-2/6, II-2/9 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2019-03-10**.

Issued at **Høvik** on **2017-01-16**

DNV GL local station:
Sandefjord

Approval Engineer:
Tessa Biever

Notified Body
No.: **0575**

for **DNV GL AS**

Vidar Dolonen
Head of Notified Body

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id:
Certificate No: **MEDB00001SA**

Product description

"JOTACOTE F60"
A two component polyamide cured epoxy coating containing Part A (base) and Part B (curing agent).
Mixing ratio A:B = 4:1 (by volume).
Relative density 1.52 g/cm^3.
Maximum coating thickness is 0.1 mm.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire. Approved for use throughout the accommodation.

Approved for use as paint systems on a metallic substrate with thickness of at least 1.125 mm.

Approved color (tested color): light pink
Organical content: 72,53 wt%

The product satisfies the requirement for maximum calorific value (ref. Solas Chapter II-2, Reg 5.3.2.2) without further testing.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and Annex 2 item 2.2 and 2.3.

Marking of product

The product or packing is to be marked with name and address of the manufacturer, type designation, Mark of Conformity and USCG approval number if applicable (see front page).