

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of the Kingdom of Norway.

This is to certify:**That the Primary deck coverings**

with type designation(s)
weber.floor 4686N Marine Extra Light

Issued to

Weber Saint-Gobain Byggevarer AS
OSLO, Norway

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2015/559,**

Annex A.1, item No. A.1/3.1 and Annex B, Module B in the Directive; SOLAS 74 as amended, Regulation II-2/4, II-2/6 & X/3, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2021-11-13**.

Issued at **Høvik** on **2016-11-14**

DNV GL local station:
Station Oslo Maritime and CAP

Approval Engineer:
Tomasz Werchowicz



Notified Body
No.: **0575**

for **DNV GL AS**

.....
Vidar Dolonen
Head of Notified Body

Job Id:
Certificate No: **MEDB00001VK**

Product description

“weber.floor 4686N Marine Extra Light”

is a polymer modified cement based levelling and fine smoothing compound. It is supplied as a lightweight one-component dry powder for hand application.

Max. thickness: 32 mm
Mass per unit area: 0.65 kg/m² per 1 mm of layer thickness
Mixing ratio: 4.5 liter of water per 10 kg of powder

Application/Limitation

Primary deck covering, not generating excessive quantities of smoke nor toxic products in fire.

The product may also be used as floor covering.

Not to be used as an integrated part of horizontal class A division unless tested as such.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and Annex 2, item 2.2.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire-technical rating, Mark of Conformity and USCG approval number (see first page).