DNV·GL

Certificate No:
MEDB00002C9

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: floor coverings

with type designation(s)
PCI Carraflex®

Issued to
PCI Augsburg GmbH
Augsburg, Germany

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2017/306,**
item No. MED/3.18c. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2022-10-23**.

Issued at **Hamburg** on **2017-10-24**

DNV GL local station:
Augsburg

Approval Engineer:
Timo Linn

Notified Body
No.: **0098**

for **DNV GL SE**

Sven Dudszus
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.
This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.
Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

"PCI Carraflex"
Consisting of dry mortar mix with special cement and PCI polymers.

Max. applied thickness:	2,8 mm
Density :	1,35 Kg/dm³
Maximum organic content:	6%
Approved colour:	white

For further details see test report as referred below.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor coverings on non-combustible substrate with a greater thickness than 25mm.

Several layers of floor coverings are acceptable provided that each layer is approved according to the Marine Equipment Directive and bear the mark of Conformity.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation
Test Report no. 20171019/01 dated 31th of July 2017 from MPA Dresden, Germany.

Tests carried out
Tested according to IMO 2010 FTP Code Annex 1, Part 5 and in compliance with Annex 2, Item 2.2.

Marking of product
The product or packing is to be marked with name and address of manufacturer, type designation, fire technical rating, Mark of Conformity and USCG approval number (see first page).