

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: floor coverings

with type designation(s)
Floor covering Type 620720

Issued to
Jingjiang Yatai Marine Resource Co., Ltd.
Jingjiang City, China

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2017/306,**
item No. MED/3.18c. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000
HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2022-11-01.**

Issued at **Hamburg** on **2017-11-02**

DNV GL local station:
Jiangyin

Approval Engineer:
Pavel Golyshev



Notified Body
No.: **0098**

for **DNV GL SE**

Sven Dudzsus
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

"Floor covering Type 620720"

Marine rubber/ PVC floor coating, mainly composed of PVC resin powder, calcium silicate, rubber, plasticizer and stabilizer and covered on the surface with printed colour film and abrasion resistant layer.

Nominal density: 1650 kg/m³

Applied thickness range: 2.0 mm – 3.0 mm

Maximum organic content: 36%

For further details see test reports as referred below.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor coverings on any low flame-spread floor covering, steel or non-combustible material.

Several layers of floor coverings are acceptable provided that each layer is approved according to the Marine Equipment Directive and bear the mark of Conformity.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Floor covering with 2.0 mm thickness is approved for all colour variations.

Approved colour for floor covering with 3.0 mm thickness: yellow.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report nos. FT13020 dated 28th of January 2013, FT13019 dated 30th of January 2013 and FT17058 dated 13th of April 2017 all issued by Far East Fire Testing Centre, Shanghai, China.

Tests carried out

Tested according to IMO Res. MSC.307(88) – 2010 FTP Code, Annex 1, Parts 2 and 5.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire technical rating, Mark of Conformity and USCG approval number (see first page).