

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Winches for survival craft and rescue boats: (d) rescue boats

with type designation(s)
W20R.FAM2

Issued to

Global Davit GmbH
BASSUM, Niedersachsen, Germany

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2017/306**,
item No. MED/1.41d. SOLAS 74 as amended, Regulation III/4, III/16, III/17, III/23, III/24, III/34, X/3, LSA Code and 2000 HSC Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2023-06-11**.

Issued at **Hamburg** on **2018-06-10**

DNV GL local station:
Bremerhaven

Approval Engineer:
Frank Poetsch



Notified Body
No.: **0098**

for **DNV GL SE**

Sven Dudsus
Head of Notified Body

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Job Id: **344.1-007748-2**
Certificate No: **MEDB00003MM**

Product description

Winches for rescue boats, winch types W20LR.FAM2

Designer

MDO – Maritime Design Office B.V.
Leusden Utrecht, The Netherlands

Application/Limitation

The W20LR.FAM2 includes lifeboat and rescue boat winches allowing an output torque of maximum 20 kNm. The winches are suitable for 50 and 60 Hz and hoist their load with rope speeds exceeding 10 alternatively 36 m/min. The gravity lowering speed is between 80 and 120 m/min. Each drum section has a length of 200-700 mm. The design temperature is min. -20°C. The family is shown on the attached drawing 7-0226.

Type Examination documentation

is based on the following drawings, verified with DNVGL Job ID: MCADE698-P261.1G-1 (WSZ, dd 2017-05-17)

Tests carried out

According IMO Resolutioon MSC.81(70), amended up to MSC.323(89), Part1, Regulation 8.1.
Type test Report No.: 1264A01 dd 2017-04-05