

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

**That the Surface materials and floor coverings with low flame-spread characteristics:
Adhesives**

with type designation(s)
Kiilto M1000ECO

Issued to

Kiilto Oy
LEMPÄÄLÄ, Finland

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2017/306,**

**item No. MED/3.18e. SOLAS 74, Reg. II-2/3, II-2/5, II-2/9 & X/3, IMO MSC/Circ. 1120, 2000
HSC Code 7 and IMO 2010 FTP Code**


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2023-03-13**.

Issued at **Høvik** on **2018-03-14**

DNV GL local station:
Turku

Approval Engineer:
Tessa Biever



Notified Body
No.: **0575**

for **DNV GL AS**

Roald Vårheim
Head of Notified Body



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Job Id: **344.1-000602-27**
Certificate No: **MEDB00003YF**

Product description

"Kiilto M1000ECO"

is an acrylic dispersion flooring adhesive.

Application/Limitation

Approved for use as a flooring adhesive with low flame spread characteristics.

Maximum amount of adhesive (wet) is 275 g/m², laid on non-combustible surfaces.

Maximum gross calorific value shall be documented separately where applicable, ref. SOLAS Chapter II-2 Reg. 5.3.2.

Each product is to be supplied with its manual for installation and use.

Type Examination documentation

Test Report File PFB10056, serial no. 13737 dated 17 December 2012 from Danish of Fire and Security Technology, Hvidovre, Denmark.

Tests carried out

Tested according to IMO 2010 FTP Code Part 5.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation and the MED Mark of Conformity (see first page).