

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

**That the Surface materials and floor coverings with low flame-spread characteristics:
decorative veneers**

with type designation(s)
TP4025 Type Aluminum Foil Bond Tape

Issued to
SHANGHAI TOPMOST IMP.& EXP. CO.,LTD.
Shanghai, China

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2018/773,**
item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000
HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2023-11-26.**

Issued at **Hamburg** on **2018-11-27**

DNV GL local station:
Shanghai

Approval Engineer:
Timo Linn



Notified Body
No.: **0098**

for **DNV GL SE**

Sven Dudzsus
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Job Id: **344.1-008341-1**
Certificate No: **MEDB0000492**

Product description

" TP4025 Type Aluminum Foil Bond Tape "

Construction: 40µm aluminum foil coated with flame retardant acrylic adhesive, with 90µm strippable kraft paper at the back manufactured by Jiangyin Bond Tape Technology Corporation.

Adhesive:

Flame-Retardant Acrylic Adhesive, Manufactured by BondTape Technology Corporation

Max. applied thickness: 1.3 mm

Density : 1.0 Kg/dm³

Maximum organic content: None

Approved colour: Silver

For further details see Type Examination documentation below.

Applications/Limitations

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as decorative veneer on non-combustible substrate.

The product satisfies the requirement for maximum calorific value (ref. SOLAS Chapter II-2, Reg 5.3.2.2) without further testing

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code Annex1 Part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test reports no. FT18223 dated 2018-09-28 from Far East Fire Testing Centre, China.

Tests carried out

Tested according to IMO 2010 FTP Code Annex1 Part 5, and in compliance with Annex 2 item 2.2 and 2.3.

Marking of product

The product or packing is to be marked with name and address of the manufacturer, type designation, the Mark of Conformity and USCG approval if applicable (see first page).