

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the Release mechanism for lifeboats and rescue boats (launched by a fall or falls)

with type designation(s)
CSAFE5 MKII

Issued to

Vanguard (Nantong) F.R.P. Co., Ltd.
Nantong, Jiangsu, China

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2018/773**,
item No. MED/1.26a. SOLAS 74 as amended, Reg. III/4, III/16, III/34 & X/3, LSA Code and 2000 HSC Code 8


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2023-09-11**.

Issued at **Høvik** on **2018-09-12**

DNV GL local station:
Nantong

Approval Engineer:
Mats Asvald Innstø



Notified Body
No.: **0575**

for **DNV GL AS**

Roald Vårheim
Head of Notified Body



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.
This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.
Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

Release mechanism for lifeboat

- Safe Working Load, SWL= 5 ton
- Max length of operating cables = 12 m
- Hang-off arrangement SWL = 4.5 ton

Type/Name of Hydrostatic locking device : Hydrostatic Release Unit

Type/Name of Release handle device : Release Handle Unit

Application/Limitation

- Grades of materials as stated on drawings are to be delivered with makers product certificates (3.1).
- The various components transferring the load like wires, shackles, hooks, etc. are to comply with international standard or code and are to be delivered with manufacturer's certificate, confirming a safety factor minimum 6 compared to the sustained load.
- Falls to be used with the launching appliance shall be of rotation-resistant and corrosion-resistant steel wire rope.
- Support to hull structure is not included in this examination and shall be evaluated separately.

Type Examination documentation

Tests carried out

Prototype testing according to IMO Resolution MSC.81(70) as amended including IMO Res. MSC.321(89) carried out 2018-08-14 through 16 and witnessed by DNV GL Nantong.

Marking of product

Marking shall be implemented in accordance with the LSA Code, item 1.2.2.9 and the Directive:

- Type designation, manufacturer name and serial number
- Maximum Working Load, MWL

END OF CERTIFICATE