

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the "B" Class divisions, fire integrity

with type designation(s)
SC-753P (B-15 Class Ceiling Panel)

Issued to

Sejin Technical Industries Co., Ltd.
Yongsan-si, Gyeongsangnam-do, Republic of Korea

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2018/773**,
item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2.3.4 & II-2/9 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2022-02-27**.

Issued at **Høvik** on **2019-06-25**

DNV GL local station:
Gimhae Station

Approval Engineer:
Karolina Kusmider



Notified Body
No.: **0575**

for **DNV GL AS**

Roald Vårheim
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

"SC-753P (B-15 Class Ceiling Panel)"

composed of 25 mm thick mineral wool core, with nominal density of 80 kg/m³ (manufactured by Byucksan Co., Ltd.), covered with 0.55 mm thick perforated steel sheets on exposed side.

Steel perforation: Ø = 1.8 mm, c/c distance = 10 mm

The panels are fixed to each other by means of tongue-and-groove joint and in addition to 1 mm thick main runners and by means of small self-tapping screws/pop-rivets Ø3.2 mm with spacing 300 mm.

The shorter sides of the panels are connected by means of connection profile which is made of a 0.6 mm thick steel profiles with total width of 100 mm.

The ceiling is connected to the steel deck by means of steel Ø8 mm hanger sets that are welded from one side to the deck and connected to main runners from another side.

On top of the panels, a layer of 50 mm thick mineral, with nominal density of 80 kg/m³ (manufactured by Byucksan Co., Ltd.), is placed.

Total panel thickness: 25 mm + 50 mm

For further details, please see drawing listed under Type Examination documentation below.

Application/Limitation

Approved for use as a horizontal fire retarding division of class B-15.

Max. panel width: 300 mm

Max. distance between main runners: 1400 mm

Max. distance between main runner and connection profile/bulkhead: 300 mm

Max. spacing between hanger sets along the main runners: 1200 mm

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire-technical rating, the MED Mark of Conformity and USCG approval number if applicable (see first page).