

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Fire Doors

with type designation(s)
HLMB15K Type Class B-15 Fire Door

Issued to

Tianjin Huali Thermal Insulation Building Material Co., Ltd.
TIANJIN, China

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2019/1397**,
item No. MED/3.16. SOLAS 74 as amended, Regulation II-2/9, IMO 2010 FTP Code and IMO MSC.1/Circ.1511, IMO MSC.1/Circ.1319


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2025-06-15**.

Issued at **Hamburg** on **2020-06-16**

DNV GL local station:
Tianjin

Approval Engineer:
Karolina Kusmider



Notified Body
No.: **0098**

for **DNV GL SE**

Gerhard Aulbert
Head of Notified Body

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

"HLMB15K"

is a class B-15 single-leaf fire door. The door leaf is composed from the exposed side of 0,7 mm thick steel plate, 36 mm thick rock wool of 150 kg/m³ nominal density, THY-150 type, manufactured by Tianjin Huali Thermal Insulation Building Material Co., Ltd and 0,7 mm thick steel plate. In addition, there is one layer of 0,8 mm thick stainless steel material rimmed at the perimeter of the door leaf. The insulation material inside the door leaf is fixed by the adhesive.

Total door leaf thickness: 38 mm.

The door frame is a four-sided door frame made by steel plate of 1,5 mm filled in the interior with ceramic wool insulation. The door frame may be welded or bolted (ST4.2x12 self-tapping screws spaced maximum 500 mm apart) to the bulkhead.

The door leaf may be fitted with a glazed opening constructed from 6 mm fireproof glass, 17 mm fireproof solution and 12 mm glass, produced by Qinhuangdao City Haigang District Yuehua Industrial Technical Factory. Further, there is a louvered escape located at the bottom of the door leaf and a fireproof door lock C-1 type from Nantong Hujiang Locks Co., Ltd, installed at the door leaf, located 1000 mm from the bottom. The door leaf is attached to the door frame by three 5" hinges.

For further details refer to the test reports listed under Type Examination documentation below.

Application/Limitation

Approved for use as an integrated part of fire retarding division of class B-15.

Max. size of a door leaf (W x H): 925 mm x 2108 mm

Max. clear opening (W x H): 900 mm x 2100 mm

Max. clear opening of a glazed opening (W x H): 450 mm x 450 mm

Max. size of a louvered escape (W x H): 425 mm x 525 mm

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test Report No. FT15210 dated 2015-06-16 from Far East Fire Testing Centre, Shanghai, China.

Tests carried out

Tested according to IMO Resolution MSC.307(88) - IMO FTP Code Annex 1, Part 3.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire technical rating (see first page).