

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

## This is to certify:

**That the Launching appliances using fall (davits)**

with type designation(s)  
**PLR-12005**

Issued to

**Vestdavit AS**  
**LAKSEVÅG, Norway**

is found to comply with the requirements in the following Regulations/Standards:  
Regulation **(EU) 2019/1397**,  
**item No. MED/1.21. SOLAS 74 as amended, Regulation III/4, III/23, III/33, III/34 & X/3,**  
**LSA Code and 2000 HSC Code 8**


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2025-05-25**.

Issued at **Høvik** on **2020-05-26**

DNV GL local station:  
**Bergen**

Approval Engineer:  
**Mats Asvald Innstø**



Notified Body  
No.: **0575**

for **DNV GL AS**

**Roald Vårheim**  
**Head of Notified Body**



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



## Product description

Rescueboat Davit with;

- Maximum Working Load, MWL = 12 000 kg
- Minimum Breaking Load of Wire Rope, MBL = 72 000 kg
- Wire Rope Diameter = 25 mm / 28 mm

## Application/Limitation

- Grades of materials as stated on drawings are to be delivered with makers product certificates (3.1).
- The various components transferring the load like wires, shackles, hooks, etc. are to comply with international standard or code and are to be delivered with manufacturer's certificate, confirming a safety factor minimum 6 compared to the sustained load.
- Falls to be used with the launching appliance shall be of rotation-resistant and corrosion-resistant steel wire rope.
- Installation, on-board testing (MSC.81(70) part.2), support to the deck structure, and connection to power supply are not included in this examination and shall be accepted by attending surveyor in each case.

## Type Examination documentation

|             |            |                               |
|-------------|------------|-------------------------------|
| 116325      | 2          | PLR-12005 General Arrangement |
| 116340      | 4          | Davit frame welded PLR-12005  |
|             | 20.08.2014 | Drawing revision list         |
| VD-TM-91719 | 3          | Technical Manual              |
| 1773781     | A5         | Electric diagrams             |
| A-15273     | 1          | Emergency low ass hyd         |
| A-15357     | 3,1        | Davit hydraulic               |
| A-15358     | 3,1        | DECK hydraulic                |

## Tests carried out

Prototype tested in accordance with IMO Resolution MSC.81(70) Part 1.

## Marking of product

Marking shall be implemented in accordance with the LSA Code, item 1.2.2.9 and the Directive:

- Type designation, manufacturer name and serial number
- Maximum Working Load, MWL

## END OF CERTIFICATE