

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the "B" Class divisions, fire integrity

with type designation(s)
HS-B3 Type Class B-15 Bulkhead

Issued to

Jiangyin Haisheng Marine Outfitting & Decoraton Co., Ltd.
Jiangyin, China

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2019/1397**,
item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1581


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2025-03-09**.

Issued at **Hamburg** on **2020-03-10**

DNV GL local station:
Jiangyin CMC

Approval Engineer:
Marcin Tobiasz



Notified Body
No.: **0098**

for **DNV GL SE**

Gerhard Aulbert
Head of Notified Body

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

"HS-B3 Type Class B-15 Bulkhead"

consists of panels, on each side composed of 0.6 mm thick galvanized steel plate, insulated with KMD-Y type rock wool produced by Tianchang KMD New Insulation Materials Co. Ltd. (nominal density 120 kg/m³ and thickness 48.5 mm). The galvanized steel plates and insulation are glued together with adhesive PAPU-30 type from Jingjiang Green Functional Material Co., Ltd. The panels are connected at joints by wedges (30 mm depth).

Total thickness of panels is 50 mm.

The panels may include longitudinal cable ducts in size 40 x 20 mm (W x H).

For further details, see documentation listed under Type Examination documentation below.

Application/Limitation

Approved for use as a vertical fire retarding division of class B-15.

Maximum panel size: 600 mm x 2460 mm (width x height).

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report no. FT18314 dated 14 January 2019 from Far East Fire Testing Centre, Shanghai, China.

Drawing No. HS-B3-T0 from Manufacturer.

Drawing No. HS-B3-T1 from Manufacturer.

Drawing No. HS-B3-T1-1 from Manufacturer.

Drawing No. HS-B3-T2 from Manufacturer.

Tests carried out

Tested according to IMO Resolution MSC.307(88) – 2010 FTP Code Annex 1, Part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating and the MED Mark of Conformity (see first page).