DNV·GL

Certificate No:
MEDB00006KV

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the A & B Class divisions fire integrity: B class divisions.

with type designation(s)
B25AXY Type B-0 Class Bulkhead

Issued to
Jiangsu Haojun Huake Housing Industrial Co., Ltd.
Jingjiang, China

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2020/1170,**
item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1581

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-02-11**.
Issued at **Hamburg** on **2021-02-12**

DNV GL local station:
Jiangyin NB & CMC

Approval Engineer:
Karolina Kusmider

Notified Body
No.: **0098**

for **DNV GL SE**

Christine Mydlak-Roeder
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004, and amended by Decision No 1/2018 dated February 18th, 2019.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.
This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.
Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

"B25AXY Type B-0 Class Bulkhead"
Bulkhead panels composed of an insulation core of 23.8 mm YG-2 type rock wool with density of 120 kg/m^3 (manufactured by Changzhou Thermal Insulation Material Factory Co., Ltd.), covered with 0.6 mm galvanized steel plates on both sides. The rock wool and steel plates are glued together with adhesive of PAPU-03 type (manufactured by Jingjiang Green Functional Material Co., Ltd). The panels are connected to each other by means of node joints fitted at the ends of each panel. The joint depth in way of the nodes were 22 mm. The back plate of product is perforated (ø2.5 mm hole with 5 mm spacing).

Total thickness of the panels is 25 mm.

For further details see drawing listed under Type Examination documentation below.

Application/Limitation

Approved for use as a vertical fire retarding division of class B-0.

Max. panel size is 700 mm x 2970 mm (W x H).

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test Report No. FT20046 dated 9 April 2020 from Far East Fire Testing Centre, Shanghai, China.

Drawing No. Q354HK1-00SY (12 pages) dated 4 January from manufacturer.

Tests carried out

Tested according to IMO Resolution MSC.307(88) – 2010 FTP Code Annex 1, Part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, MED Mark of Conformity and USCG approval number if applicable (see first page).