

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB00007GT

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: decorative veneers

with type designation(s)

ALU COATING, GV COATING, TEXALU200 COATING, TEXALU400 COATING, Z COATING

Issued to

ARLY

Creil, France

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2021/1158,

item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-09-15**.


Issued at **Høvik** on **2021-09-16**

DNV local station:

France CMC

Approval Engineer:

Nanna Martine Jacobsen



Notified Body
No.: **0575**

for **DNV AS**

Sverre Olav Bergli
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“ALU COATING, GV COATING, TEXALU200 COATING, TEXALU400 COATING and Z COATING”, are surface coating materials for insulation.

The base insulation material consists of mineral wool tested and approved as non-combustible types and having a nominal density of minimum 15 kg/m³. The insulation can be faced with:

Surface material	Colour	Description	Total thickness / grammage
ALU COATING	Aluminium	18 µm aluminium foil reinforced glass fibre scrim glued to the insulation.	0.018 mm 80 g/m ²
GV COATING	White	White glass fabric glued to the insulation.	0.18 mm 220 g/m ²
TEXALU200 COATING	White or aluminium	White glass fabric and 18 µm aluminium foil glued to the insulation	0.2 mm 270 g/m ²
TEXALU400 COATING	White or aluminium	White glass fabric and 18 µm aluminium foil glued to the insulation	0.4 mm 485 g/m ²
Z COATING	Grey	Flexible rubber-based polymer formulated with chlorosulfonated polyethylene glued to the insulation.	1.0 mm 1500 g/m ²

Application /Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as decorative veneer on non-metallic, non-combustible substrate with density of at least 15 kg/m³.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

The products satisfy the requirements for maximum calorific values (ref. SOLAS Chapter II-2, Reg 5.3.2.2) without further testing.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report No. DO-20-1742\B-R1 dated 2 March 2020 from CREPIM, Bruay-La-Buissière, France.
Test report No. DO-20-2143\A-R1 dated 17 August 2020 from CREPIM, Bruay-La-Buissière, France.
Test report No. DO-20-1779\C-R1 dated 6 March 2020 from CREPIM, Bruay-La-Buissière, France.
Test report No. DO-20-1586\D-R1 dated 15 January 2020 from CREPIM, Bruay-La-Buissière, France.
Test report No. DO-21-3229\A-R1 A dated 27 August 2021 from CREPIM, Bruay-La-Buissière, France.

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and Annex 2 item 2.2 and 2.3, or part 2.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, the MED Mark of Conformity and USCG approval number if applicable (see first page).