EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB00007HJ

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: decorative veneers

with type designation(s)
Larcore® HPL

Issued to
ALUCOIL, S.A.
Miranda de Ebro, Burgos, **Spain**

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2020/1170,**
item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-07-18**.

Issued at **Hamburg** on **2021-07-19**

DNV local station:
Area NB/CMC Iberia

Approval Engineer:
Timo Linn

Notified Body
No.: **0098**

for **DNV SE**

Christine Mydlak-Roeder
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004, and amended by Decision No 1/2018 dated February 18th, 2019.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.
This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.
Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

The composite panel Larcore® HPL consists of the following products:
- Larcore Primer / Primer, 6 mm to 25 mm thick (EC-Type Examination Certificate No. 118.288 / 1st Amendment)
- 3M Double Coated Tissue Tape, 0.15 mm thick (manufacturer: 3M Spain, S.L.)
- Formica HPL, 0.7 mm thick (manufacturer: Formica S.A.)

Total thickness of the composite panel: 7 mm up to 26 mm.
Total surface weight of the composite panel: 5.74 kg/m² (7 mm) to 8.26 kg/m² (26 mm).
HPL panel colour (fire-facing side): light blue

For further details refer to the documentation listed below under “Type Examination documentation”.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

The product satisfies the requirement for maximum calorific value (ref. SOLAS Chapter II-2, Reg 5.3.2.2) without further testing.

Each product is to be supplied with its instructions for installation, use and maintenance.

Type Examination documentation

- Test Report No. ICL/HI6/5950 Rev. 2 issued by "Interscience Fire Laboratory", Hampshire PO12 2AG (UK), dated on 27.07.2016.
- Test Report No. ICL/HI6/5949 Rev. 2 issued by "Interscience Fire Laboratory", Hampshire PO12 2AG (UK), dated on 27.07.2016.
- Test Report No. ICL/HI6/5952 Rev. 2 issued by "Interscience Fire Laboratory", Hampshire PO12 2AG (UK), dated on 26.07.2016.
- Test Report No. ICL/H16/5951Rev. 2 issued by "Interscience Fire Laboratory", Hampshire PO12 2AG (UK), dated on 26.07.2016.
- Letter of the company Alucoil S.A. (Mr. I. Zarate Villanueva) dated on 11.08.2016.

Tests carried out

Tested according to IMO Res. MSC.307(88) - 2010 FTP Code, Annex 1, Part 5 and 2

USCG Approval Category (Module B) number

This product has been assigned a U.S. Coast Guard Module B number 164.112/EC0098 to note type approval to Module B only as it pertains to obtaining US Coast Guard approval as allowed by the “Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment” signed February 27th,2004 and amended by Decision No.1/2018 dated February 18th, 2019.

Marking of product

The product or packing is to be marked with:
- name and address of manufacturer,
- type designation,
- fire technical rating and
- the MED Mark of Conformity (see page 1) and

USCG approval number, if applicable.