

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB000080J

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: floor coverings

with type designation(s)
HY16 Type PVC FLOOR

Issued to

Jiangyin Julin New Material Co., Ltd.
Jiangyin City, China

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2021/1158,

item No. MED/3.18c. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2027-06-12**.

Issued at **Hamburg** on **2022-06-13**

DNV local station:
Jiangyin NB & CMC

Approval Engineer:
Timo Linn



Notified Body
No.: **0098**

for **DNV SE**

Christine Mydlak-Roeder
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

"HY16 Type PVC Floor"

Floor covering consisting of 3mm thick (PVC) floor in dark grey, affixed with an approved adhesive on a 12mm calcium silicate board.

Density: 1580kg/m³

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor covering on any low flame-spread floor covering, steel or non-combustible material.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code Part 5 and to be approved according to the Marine Equipment Directive and bear the MED Mark of Conformity.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test Report No. FT16090 issued on 2015-02-16 and FT16332 issued on 2016-08-17 by Far East Fire Testing Centre.

Certificate has been renewed based on the MED B Certificate 14731-15 HH

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and 2.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, the MED Mark of Conformity and USCG approval number if applicable (see first page).