

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB000089V

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the **A & B Class divisions fire integrity: B class divisions.**

with type designation(s)
JCP-L3Q Type Class B-15 Light Scaleboard

Issued to

Jiangsu Hailu Technology Incorporated Corporation
JIANGYIN, JIANGSU, China

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2022/1157**,
item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO
MSC/Circ.1120 and IMO MSC.1/Circ.1581


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2028-03-16**.

Issued at **Hamburg** on **2023-03-17**

DNV local unit:
Jiangyin NB & CMC

Approval Engineer:
Karolina Kusmider



Notified Body
No.: **0098**

for **DNV GL SE**

Christine Mydlak-Roeder
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“JCP-L3Q Type Class B-15 Light Scaleboard”

consists of scaleboard mounted with 90 mm air gap to the structural steel bulkhead.

The scaleboard is composed of 0.35 mm thick steel plate on both sides, insulated with KMD-Y type rock wool (nominal density 120 kg/m³ manufactured by Tianchang KMD New Insulation Materials Co., Ltd.).

The steel plates and insulation are glued together with the adhesive YB2002X/YB8001 from Shanghai Ningrui Adhesive Science & Technology Development Co., Ltd. The seam node is notch type (27 mm in depth).

Total panel thickness: 25 mm.

The scaleboard is mounted in an enclosed frame made of 65 mm x 65 mm x 6 mm steel L-profiles. The pressing frame, made of 30 mm x 30 mm x 3 mm steel L-profile, is fitted around the inside frame. The pressing frame is connected to the enclosed frame by tack welds.

For further details, see documentation listed under Type Examination documentation below.

Application/Limitation

Approved for use as a vertical fire retarding division of class B-15.

Maximum scaleboard panel size: 600 mm x 2460 mm (WxH)

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Tests carried out

Tested according to IMO 2010 FTP Code Part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, the MED Mark of Conformity and USCG Approval Number if applicable (see first page).