EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB00008TW

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: decorative veneers

with type designation(s)
Iacore® DG5 Finish

Issued to
ALUCOIL, S.A.
Miranda de Ebro, Burgos, Spain

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2023/1667,**
item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2028-11-30**.

Issued at **Hamburg** on **2023-12-01**

DNV local unit:
Area NB/CMC Iberia

Approval Engineer:
Roland Priebe

Notified Body
No.: **0098**

for **DNV GL SE**

Mydlak-Röder, Christine
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004, and amended by Decision No 1/2023 dated May 26th, 2023.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.
This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment.
This certificate remains valid unless suspended, withdrawn, recalled or cancelled.
Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

lacore® DG5 Finish is an aluminum honeycomb panel lacore® coated with DG5 (manufacturer: Euromax Coated Products B.V., NL-6045 JG Roermond).
The lacore® 40 mm panel consists of aluminum honeycomb with 1 mm aluminum sheets on both sides.

Aluminum honeycomb panel lacore®:

Thickness (total)	5.5 mm to 40 mm
Weight	3.22 kg/m² (5.5 mm) to 7.49 kg/m² (40 mm)
Thickness of cover sheet	0.5 mm (5.5 mm) to 1 mm (40 mm)

Coating DG5:

Thickness	23 ± 4 µm
Colour	Various
Organic content	≤ 55 %

For further details refer to the documentation listed below under “Type Examination documentation”.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code Part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report No. ICL/H187/7896 Rev.1 dated 2017-11-24 from Interscience Fire Laboratory, Hampshire, UK.
Test report No. ICL/H18/9642 dated 2018-07-25 from Interscience Fire Laboratory, Hampshire, UK.

Technical Data “lacore® 40 mm” from manufacturer Alucoil
Finish specification “DG5 2L COASTAL” from manufacturer Alucoil

Tests carried out

Tested according to IMO 2010 FTP Code Part 5

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, MED Mark of Conformity and USCG approval number if applicable (see first page).