

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB00008V6

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

that the Surface materials and floor coverings with low flame-spread characteristics: decorative veneers

with type designation(s)
ArmaComfort Barrier P ALU

issued to

Armacell Italia S.r.l.
Leini, Italy

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2023/1667,
item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO
2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2029-04-09**.

Issued at **Hamburg** on **2024-04-10**

DNV local unit:
Italy/Malta CMC

Approval Engineer:
Tessa Biever



Notified Body
No.: **0098**

for **DNV SE**

Mydlak-Röder, Christine
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“ArmaComfort Barrier P ALU”

Is composed of a white to light grey heavy mass for acoustic insulation (Polymeric compound (EVA/IIR) with self-extinguishing mineral fillers (barium sulphate, aluminium hydrate) with an aluminium layer on the top surface, marked as: “Barrier P ALU 5 mm”.

Overall thickness: 4,7 – 5.0 mm.

Weight per unit area: 10 kg/m²

For further details see Type Examination documentation below.

Application/Limitation

Approved for use as low flame spread material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor covering on any metallic and non-combustible base.

Restricted application: Fire against the aluminium layer.

Approved color: White to light grey with aluminium (top layer)

Max. organic content: 15 wt%

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the MED Mark of Conformity.

Several layers of floor coverings are acceptable provided that each layer is approved according to the Marine Equipment Directive and bear the MED Mark of Conformity.

The product satisfies the requirement for maximum gross calorific value (ref. SOLAS II-2/5.3.2.2) without further testing.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report No. SL/Z-775/FTP5/0867a/2023 dated 11 October 2023 from SYCHTA LABORATORIUM, Police, Poland.

Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and Annex 2 Item 2.2 and 2.3.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, MED Mark of Conformity and USCG approval number if applicable (see first page).