

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB000090G

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

that the Surface materials and floor coverings with low flame-spread characteristics: floor coverings

with type designation(s)
Haydeck Epoxy Flooring

issued to

Shanghai Aosheng Metal Products Co., LTD.
Shanghai, China

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2024/1975,

item No. MED/3.18c. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2029-09-18**.

Issued at **Hamburg** on **2024-09-19**

DNV local unit:
Shanghai

Approval Engineer:
Izabela Misztal



Notified Body
No.: **0098**

for **DNV SE**

Mydlak-Röder, Christine
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004, and amended by Decision No 1/2023 dated May 26th, 2023.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“Haydeck Epoxy Flooring”

is a four-layer floor covering consisting of HayDeck Primer 605, HayDeck WFE, HayDeck FE and HayDeck WRL.

Layer	Product	Density	Thickness
1 st layer	HayDeck Primer 605	1.4 ± 0.1 kg/m ³	0.1 mm
2 nd layer	HayDeck WFE	2.1 kg/m ³	44.8 mm
3 rd layer	HayDeck FE	1.8 kg/m ³	5 mm
4 th layer	HayDeck WRL	1.3 ± 0.05 kg/m ³	0.1 mm

Max. thickness: 50 mm

Density: 2125.5 kg/m³

For further details see documents under Type Examination documentation below.

Application/Limitation

Approved for use as low flame spread material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for all colour variations.

Maximum organic content:

HayDeck Primer 605 53 %

HayDeck WFE 45 %

HayDeck FE 55 %

HayDeck WRL 73 %

Approved for use as decorative veneer on a metallic substrate with thickness of at least 2.1 mm.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report no. AJFS2404004182FF dated 06 June 2024 from SGS, Nantong, Jiangsu, China.

Test report no. AJFS2404004183FF dated 06 June 2024 from SGS, Nantong, Jiangsu, China.

Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and 2.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, the MED Mark of Conformity and USCG Approval Number if applicable (see first page).