

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB0000921

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:

that the **A & B Class divisions fire integrity: B class divisions.**

with type designation(s)

HL-TJXM Type B-15 Class Ceiling Access Door

issued to

Jiangsu Hailu Technology Incorporated Corporation
JIANGYIN, JIANGSU, China

is found to comply with the requirements in the following Regulations/Standards:

Regulation (EU) 2023/1667,

item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO
MSC/Circ.1120 and IMO MSC.1/Circ.1581


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2029-08-21**.

Issued at **Hamburg** on **2024-08-22**

DNV local unit:
Jiangyin NB & CMC

Approval Engineer:
Marta Kropiwnicka



Notified Body
No.: **0098**

for **DNV SE**

Mydlak-Röder, Christine
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004, and amended by Decision No 1/2023 dated May 26th, 2023.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

“HL-TJXM Type B-15 Class Ceiling Access Door”

Is a hatch composed of 39 mm thick of KMD-Y type marine rock wool (density 120 kg/m³, produced by Tianchang KMD New Insulation Materials) faced from both sides with 0.5 mm thick steel plates.

The galvanized steel plates and insulation are glued together with PAPU-30 type polyurethane adhesive from Jingjiang Green Functional Material.

The hatch is connected to the 1.5 mm thick frame by a pair of stainless-steel hinges at one side of leaf.

Fireproof sealing strips (2 mm x 20 mm) are filled around hatch leaf and frame.

The hatch leaf is equipment with a C-J type lock produced by Nantong Hujiang Marine Technology.

The thickness of door leaf in the hatch: 40 mm

For further details see documentation(s) listed under Type Examination documentation.

Application/Limitation

Approved for use as an integrated part of a horizontal fire retarding division of class B-15.

Approved for installation in the tested ceiling JCP-C2A type, produced by Jiangsu Hailu Technology Incorporated Corporation. Installation in other ceilings may be approved case-by-case. Ceiling has to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Max. clear opening of the hatch:	500 mm x 800 mm	(W x H)
Max. size of hatch leaf:	544 mm x 845 mm	(W x H)

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report No. FT22095 dated 18 August 2022 from Far East Fire Testing Centre, Shanghai, China.

Tests carried out

Tested according to IMO 2010 FTP Code Part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, the MED Mark of Conformity and USCG Approval Number if applicable (see first page).