

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB0000AYK
Revision no.:
0

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

that the **Release mechanism for: - lifeboats and rescue boats (launched by a fall or falls)**

with type designation(s)
NOA 5.5t Off-Load

issued to

Kolberg Caspary Lautom AS
Skoppum, Norway

is found to comply with the Implementing Regulation (EU) 2025/1533 for
Item no. **MED/1.26a (Row 1 of 1)**

according to the following requirements:

SOLAS 74 Reg. III/16, SOLAS 74 Reg. III/34, IMO Res. MSC.36(63)-(1994 HSC Code) 8, IMO Res. MSC.48(66)-(LSA Code) I, IMO Res. MSC.48(66)-(LSA Code) IV, IMO Res. MSC.97(73)-(2000 HSC Code) 8, IMO MSC.1/Circ.1419, IMO MSC.1/Circ.1630/Rev.2, SOLAS 74 Reg. III/4, SOLAS 74 Reg. X/3


Further details of the equipment and conditions for certification are given overleaf.

Date of issue: **2025-09-27**

Expiry date: **2030-09-26**

DNV local unit:
Sandefjord

Approval Engineer:
Kris Michael Gabriel



for **DNV AS**

Notified Body
no.: **0575**

Christine Mydlak-Röder
Head of Notified Body



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

Off-load release mechanism for lifeboat and rescue boats (launched by falls) with:

- Safe Working Load, SWL = 5500kg

Application/Limitation

- Grades of materials as stated on drawings are to be delivered with maker's product certificates (3.1).
- The various components transferring the load like wires, shackles, hooks, etc. are to comply with international standard or code and are to be delivered with manufacturer's certificate, confirming a safety factor minimum 6 compared to the sustained load.
- Falls to be used with the launching appliance shall be of rotation-resistant and corrosion-resistant steel wire rope.
- The release mechanism shall be so installed that crew members from inside the lifeboat can determine when the system is ready for lifting as per LSA Code.

Type Examination documentation

Tests carried out

Prototype tested in accordance with IMO Resolution MSC.81(70) Part 1.

Test report MSC.1/Circ.1630 performed 2025-09-25 and witnessed by DNV Norway.

Marking of product

Marking shall be implemented in accordance with the LSA Code, item 1.2.2.9 and the Directive:

- Type designation, manufacturer name and serial number
- Maximum Working Load, MWL