EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB0000BEG
Revision no.:
0

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as “Forskrift om Skipsutstyr” by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

that the **Surface materials and floor coverings with low flame-spread characteristics: - adhesives used in the construction of ’A’. ’B’ & ’C’ class divisions**

with type designation(s)
ARDEX AF 480

issued to
ARDEX Skandinavia A/S
Herlev, **Denmark**

is found to comply with the Implementing Regulation **(EU) 2024/1975** for
Item no. **MED/3.18e** (Row **1 of 1**)
according to the following requirements:
SOLAS 74 Reg. II-2/3, IMO Res. MSC.36(63)-(1994 HSC Code) 7, IMO Res. MSC.97(73)-(2000 HSC Code) 7, IMO MSC/Circ.1120, SOLAS 74 Reg. II-2/5, SOLAS 74 Reg. II-2/9, SOLAS 74 Reg. X/3

Further details of the equipment and conditions for certification are given overleaf.

Date of issue: **2025-09-19**

Expiry date: **2030-09-18**

DNV local unit:
Denmark CMC

Approval Engineer:
Helge Bjørnarå

Notified Body
no.: **0575**

for **DNV AS**

Christine Mydlak-Röder
Head of Notified Body

NORWEGIAN ACCREDITATION PROD 019

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer’s Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.
This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.
Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees (“DNV”) arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

"ARDEX AF 480",
a one component, firm-elastic adhesive for laying different types of parquet flooring.

Mass per unit area: 0.8 kg/m²
Density: 1800 kg/m³
Maximum average thickness: 0.45 mm

Application/Limitation

Approved for use as adhesive with low flame spread characteristics, not generating excessive quantities of smoke nor toxic products in fire.

Approved colour: light brown.
Maximum organic content: 30%

Maximum gross calorific value shall be documented separately where applicable (SOLAS Reg. II-2/5.3.2).

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and 2.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, and MED Mark of Conformity (see first page).