DNV·GL

Certificate No:
TAA000024M

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Peripheral Equipment

with type designation(s)
EDR-810 series

Issued to
Moxa Inc.
New Taipei City, Taiwan

is found to comply with
DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Temperature	**A**
Humidity	**B**
Vibration	**A**
EMC	**B**
Enclosure	**A**

Issued at **Hamburg** on **2018-12-11**
This Certificate is valid until **2023-12-10**.
DNV GL local station: **Kaohsiung**

Approval Engineer: **Jens Dietrich**

for **DNV GL**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-029148-1**
Certificate No: **TAA000024M**

Product description

8+2G Multiport Industrial Secure Router with switch/firewall/NAT/VPN

EDR-810-2GSFP: 8+2G-port industrial multiport secure router with frewall/NAT, -10 to 60°C operating Temperature,

EDR-810-2GSFP-T: 8+2G-port industrial multiport secure router with frewall/NAT, -40 to 75°C operating temperature,

EDR-810-VPN-2GSFP: 8+2G-port industrial multiport secure router with frewall/NAT/VPN, -10 to 60°C operating temperature

EDR-810-VPN-2GSFP-T: 8+2G-port industrial multiport secure router with frewall/NAT/VPN, -40 to 75°C operating temperature

Interface:
RJ45 Ports: 10/100BaseT(X) auto negotiation speed
Fiber Ports: 1000BaseSFP slot
Console Port: Web/Telnet/SSH/CLI, and RS-232 serial console
RESET button: Reset to default settings
LED Indicators: STATE, PWR1, PWR2, FAULT, 10/100/1000M
Alarm Contact: One relay output with current-carrying capacity of 1 A@24 VDC
Digital Inputs: 1 2-contact terminal block

Degree of protection: IP20.

Power supply: Redundant dual inputs, 24VDC.

Place of manufacture

MOXA Inc.
Fl. 4, No. 135, Lane 235, Baoqiao Rd.
Xindian Dist., New Taipei City, 23145
Taiwan

Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9, Control and monitoring systems.

The units are tested and approved for mounting on DIN-rail in groups of two or more different units on each DIN-rail.

Compass safe distance:
Standard compass: 75cm, Steering compass: 45cm.

Tests carried out

Applicable tests according to DNVGL-CG-0339, November 2016; applicable tests referenced in IACS UR E10, Rev.6; Tests section 7.1, 8.2, 8.3, 8.4 and 11.2 of IEC 60945, 4th edition (2002).

Marking of product

Maker, type designation and serial number.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of this certificate.

END OF CERTIFICATE