

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Pressure Transmitter**with type designation(s)
A-10

Issued to

WIKA Alexander Wiegand SE & Co. KG
Klingenberg, Germany

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Location classes:**

Temperature	D
Humidity	B
Vibration	B
EMC	B
Enclosure	C

Issued at **Hamburg** on **2019-07-09**This Certificate is valid until **2024-07-08**.DNV GL local station: **Augsburg**for **DNV GL**Approval Engineer: **Dariusz Lesniewski**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Sensor: thin-film on steel or piezo-resistive

Measuring ranges: 0...0.6 to 0...1000 bar

Output signal / [Power supply]:

- Current (2-wire): 4...20 mA / [DC 24 V (8...35 V)]
- Voltage (3-wire): DC 0...10 V / [DC 24 V (14...35 V)]
DC 0...5 V, 1...5 V, 0.5...4.5 V / [DC 24 V (8...35 V)]
- Ratiometric (3-wire): DC 0.5...4.5 V / [DC 5 V (4.5...5.5 V)]

Electrical connection: angular connector (DIN EN 175 301-803 A or C)
circular connector (M12x1)
cable outlet: OEM, UL 94 V-0 listed, max. length 5 m

Process connection:

- G1/2", G3/8", G1/4" male + female (/with flange connection), G1/8"
- M14x1.5, M20x1.5, R1/4", R3/8", R1/2", 7/16-20 UNF
- 1/8 NPT, 1/4 NPT male+female, 1/2 NPT
- Material (sensor, housing): stainless steel 316L

Degree of protection: IP65, IP67 (M12x1 and cable outlet)

Vibrations: 20g, sinus (25...2000 Hz); Dry Heat: +100°C; Cold: -30°C

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Application/Limitation

Only products bearing the DNV GL Mark on the product and/or product packing are certified.

Type Approval documentation

Tests carried out

Applicable tests according to class guideline DNVGL-CG-0339, November 2016.

Additional tests: [Vibrations]: 20g, sinus (25...2000 Hz); [Cold]: -30°C; [Dry Heat]: +100°C.

Marking of product

The products to be marked with:

- manufacturer name
- model name
- serial number
- power supply ratings
- DNV GL Mark on product or packing

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given



Job Id: **262.1-031172-1**
Certificate No: **TAA00002E7**

- Ensuring traceability between manufacturer's product type marking and the type approval certificate
- Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE