

# TYPE APPROVAL CERTIFICATE

## This is to certify:

**That the Temperature Sensor**

with type designation(s)  
**G3200, W3201, G3210, W3211, G3220, W3221**

Issued to

**WIKA Alexander Wiegand SE & Co. KG**  
**Klingenberg a. Main, Bayern, Germany**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft**

## Application :

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

|                    |            |
|--------------------|------------|
| <b>Temperature</b> | <b>B</b>   |
| <b>Humidity</b>    | <b>B</b>   |
| <b>Vibration</b>   | <b>B</b>   |
| <b>EMC</b>         | <b>N/A</b> |
| <b>Enclosure</b>   | <b>N/A</b> |

Issued at **Hamburg** on **2019-09-04**

This Certificate is valid until **2024-09-03**.

DNV GL local station: **Augsburg**

for **DNV GL**

Approval Engineer: **Dariusz Lesniewski**

.....  
**Joannis Papanuskas**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



## Product description

Industrial Thermometers:

G3200, W3201, G3210, W3211, G3220, W3221 (including protection pockets)

Ranges: -60°C up to 650°C

Columns (filling): Organic liquid or mercury

Material: CW614N (2.0401), CW702R (2.0460), 1.0718, 1.4571  
and special materials

Tread connections: G1/2, G3/4, M20x1.25, M20x1.5, M22x1.5, M24x2, M27x2  
and special threads

Immersion tube length: L1 = 30mm up to 250mm

## Application/Limitation

When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL RU SHIP Pt.4 Ch.9 Sec. 1.

## Type Approval documentation

### Tests carried out

Applicable tests according to Class Guideline DNVGL-CG-0339, Edition November 2016.  
Extreme vibration strain with acceleration = 5g

### Marking of product

The products to be marked with:  
- manufacturer name

### Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE