



Certificate No:
TAA000037V

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Electronic Chart System (ECS)

with type designation(s)
COSTAL E

Issued to

Telko AS
TJØME, Norway

is found to comply with
See overleaf and tests carried out.

Application :

ECS in accordance with Norwegian Maritime Authority (NMA) RSV 14-2022 and RSV 16-2022

Issued at **Høvik** on **2022-11-06**

This Certificate is valid until **2027-11-05**.

for **DNV**

DNV local unit: **East & South Norway CMC**

Approval Engineer: **Frederik Tore Elter**

Marta Alonso Pontes
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2022-09

www.dnv.com

Page 1 of 5

Product description

COSTAL E Electronic Chart System (ECS), for non SOLAS vessels, consisting of the following components:

Unit	Components	Remark
Panel Computer:	HD 16T30 DEC-MG7-3HOH1A or, HD 21T30 DEC-MG7-3HOH1A	Panel computer, including display, prosessing unit, IEC 61162-1 / LAN interface and power connection.
Panel computer to be installed with:		
Keyboard/ Trackball ¹⁾ :	BTC5100C PS/2, or Cherry G84-4100LCMGB-2 or Keytouch Panel QWERTY, and MouseTRAK B-MPIND-XROHS, or MouseTRAK B-USBID-XROHS, or Logitech Trackman Marble – ELK, or Keytouch Panel Trackball, or Cursor Controls E38-16A19D-E003, or Cursor Controls E38-16A19D-E004, or Trackball NSI TBE38NO Keytouch Panel Combo ²⁾ , or NSI RKCT92S2), or TECDIS Keypad ³⁾ (Keytouch PN17610415), or RCU-018, or NSI Rkte85B0001-W-MC11 ²⁾ , or Cursor Controls TKB08025A ¹⁾	¹⁾ Both keyboard and a trackball are required ²⁾ Combined unit ³⁾ Option
Loudspeakers(option):	DNH HP-6, or DNH HPS-6	Loudspeaker is required only when display unit does not include a buzzer and RCU-018 is not connected.
Alarm interface (option):	Telchart Alarm interface, TEA-01	Power sense relay.
Serial Interface:	Hatteland Display PCA100293-1 ⁴⁾	⁴⁾ Integrated in Panel Computer HD 16T30 DEC-MG7-3HOH1A or, HD 21T30 DEC-MG7-3HOH1A
LAN interface (option):	Intel IQ87-PLH3 Ethernet Switch: Moxa EDS-208A, Moxa EDS-308 and/or Weidmüller IE-SW-BL08-8TX	
Software Versions:		⁵⁾ May be installed ass tested and found compliant in TECDIS MED-B certification, in line with manufacturer's instructions.
TECDIS	4.8.3.x ⁵⁾	
Presantation Library	4.0.x ⁵⁾	
Telko Chart Loader	2.nn ⁵⁾	
OS	Windows 10	
Screen sender	1.xx ⁵⁾	

Application/Limitation

- COSTAL E is to be installed in accordance with manufacturers documentation. The product is based on TECDIS approval MEDB00001B0 with identical software. TECDIS documentation is to be used for equipment operation reference.
- A dual/multiple station installation of COSTAL E may function as equipment Back-up arrangements.
- COSTAL E may optionally be provided with radar overlay functionality.
- COSTAL E may optionally be provided with weather information overlay functionality. ¹⁾
- COSTAL E may optionally be provided with C-Routes routing advisory functionality.
- COSTAL E may optionally be connected to internet via "secure web-tunneling". ¹⁾
- COSTAL E may optionally support uploading of SENC delivery (CM93/3 format) via external link. ¹⁾
- COSTAL E may be optionally provided with C-Map Update Service functionality. ¹⁾
- COSTAL E may be optionally provided with Navtor NavSync chart update functionality. ¹⁾
- COSTAL E may be optionally provided with chart synchronization functionality between COSTAL E stations.
- The COSTAL E monitor may optionally be interconnected with a video source via a separate input port for presentation of video.
- COSTAL E may provide conning information to a separate monitor.
- COSTAL E may be interfaced to either RADAR or AIS, or both, for target presentation.
- The COSTAL E shall be commissioned and tested onboard according to the Installation Manual.
- COSTAL E may receive IEC 61162-1 formatted sentences (as defined in product documentation) on Ethernet in addition to binary image transfer and RTZ route transfer.

Note:

- 1) A physical disconnection device (e.g. switch) shall be provided in the vicinity of the COSTAL E – and be properly marked. Firewall is to be provided onboard. For ship external data exchange, connection is only towards remote access nodes specified by the Manufacturer.

Type Approval documentation

DNV No.	Title	Drawing No.	Rev.
20	Certificate: IEC60945, Hatteland Multi Computer HD 16T30 MMC and HD 21T30 MMC	MRA000002D	Rev.no.2
19	Report: TELKO COASTAL E Test Report, with HD 16T30 DEC-MG7-3HOH1A and HD 21T30 DEC-MG7-3HOH1A, Norwegian Maritime Authority RSV 14-2022/RSV 16-2022, IEC 61174 ed.4, IEC 62288 ed.2		30.09.22 Rev-1
17	Manual: TELKO Coastal E Installation Manual EN	Software edition: 4.8.3.x	Rev 1.2
12	Report: Hatteland - HD 21T30 IEC62288 Flicker test report HD 21T30 MMC	DOC207294-1	R02
11	Report: Hatteland - HD 21T30 IEC 62288 Conformance test report HD 21T30 MMC	DOC207293-1	R02
10	Report: Hatteland - HD 21T30 DEC IEC 62288 Minimum brightness test of EDC	DOC207119-1	R01
7	Report: Hatteland - HD 16T30 DEC IEC62288 Flicker test report HD 16T30 MMC_R02_SIGNED	DOC207285-1	R02
6	Report: Hatteland - HD 16T30 DEC Conformance test report_HD 16T30 MMC_R02	DOC207276-1	R02
5	Report: Hatteland - HD 16T30 DEC Minimum brightness test of EDC	DOC207119-1	R01

Type Approval documentation TECDIS NPS folder 344.1-0000515

DNV No.	Title	Drawing No.	Rev.
369	Manual: TECDIS Installation Manual (SW edition 4.8.3.x)		Rev 3.08
367	TECDIS TKB08025A Test Report 25-06-21		
366	Certificate: IEC 60945 DNV: Hatteland Technology AS, Monitors: HD 32T22 MVD, HD 43T22 MVD, HD 55T22 MVD	MRA0000016	Rev. 2

DNV No.	Title	Drawing No.	Rev.
312	Report: IEC60945 MS TESTING: Test Report Marine Type Approval Testing - Selected dests only Corsor Controls Silicone Rubber Keyboard with Ergonomic Trackball	TL18136	Issue 1
310	Report: IEC60945 Force: Test for marine type approval of RKTE85 keyboard	119-29851-1	
309	Report: MS Testing, IEC60945: Marine Type Approval Testing Cursor Controls Ltd. TKB08025A/RKTS13F2041-W-MC1 USB Keypad	TL20074A	Issue 3
308	Report: MS Testing, IEC60945: Test Report Marine Type Approval Testing Salt Mist Cursor Controls Ltd. TKB08025A/RKTS13F2041-W-MC1 USB Keypad	TL20074	Issue 2
307	Report: MS Testing, IEC60945: Test Report Ingress Protection Cursor Controls Ltd. TKB08025A/RKTS13F2041-W-MC1 USB Keypad	TL20074	Issue 2
302	Report: Telko IEC 62923-1:2018, IEC 62923-2:2018 and IEC 61162-450:2018 TECDIS Test Report		19th of June 2021
242	Certificate: Moxa Ethernet Switch EDS-208A	TAA000006N	Revision 1
241	Moxa and Weidmuller equivalence statement		
238	EDS-200A Corrosion Waiver (Moxa Switch)		
223	Report: TELKO Conformance test of TECDIS with IEC61174, IEC61162-450 and IEC61162-1 for RTZ route plan exchange		2
208	Report: DELTA - IEC 60945 - Corrosion - Salt Mist test	117-21066 - DANAK-1918104	
207	Report: IEC 60945 Test for Marine Type Approval E38-16A19D-E003 Trackball right-handed and E38-16A19D-E003 Trackball left handed	T208006-2 - DANAK 1914159	
181	EDS-308 309 316 series DNV Test Report		
163	Manual: TECDIS Manual EN Full		4.00 beta 4
158	Report: TECDIS IEC 61162-1 for NRM-NRX-NSR test report - signed		
151	Report: Confirmace test of TECDIS with IHO test data sets for ECDIS (S-64) - Signed		
150	Report: Confirmace test of TECDIS with IEC61174 ed-4 - Signed		
138	Report: Witnessed Conformance Test of TECDIS with IEC 61162-450 (receiving IEC 61162-1 sentences)		
137	Quick reference guide - 61162-450 in TECDIS		1
135	TECDIS IEC 61162-450 serial input validation		1
134	Quick reference guide - TelkoTranslator 1_0		1
128	Manual: Telko Conning User Manual		1
124	Report: Conformance test or TECDIS binary image transfer with IEC61162-450		
123	Report: Conformance test of TECDIS with IEC62288 2nd edition		
121	TECDIS Conning installation for fall-back arrangements		
97	Statement from ITAC - trackball B-MPIND-XROHS REV C		2015-08-10
96	Report: EMC testing og USB Mouse - Track IEC60945	SP05980	2015-11-03
92	LAN and Serial interface documentation	IQ87-PLH3 and MAX3535E	
84	Interconnection test of Moxa Multiport Serial board -IEC61162	20316	0
83	TECDIS Keypad Conformance test w/video switch	2014.03.04	1
80	Installation notes - TECDIS Keypad EN	25.02.2014	1.1
78	DNV Environmental & EMC test report: Keytouch	2008-3425	2
77	IEC60945 - Test Report: enix-2067/3076/3000/2077	Nemko E12134.04	
57	Conformance test of chart synchronization and new updating means dated 27. June 2013	27. June 2013	1
56	TECDIS Synchronization User Guide 27. June 2013	27. June 2013	1
55	TECDIS Synchronization Installation Guide 25. June 2013	25. June 2013	1
53	TECDIS Operator Manual		2.3
43	TECHNICAL REP - HATTELAND DISPLAY AS - EMC AND ENVIRONMENTAL TESTING OF MARITIME COMPUTER HT C01 STD-D100	DNV 2010-3243	4

DNV No.	Title	Drawing No.	Rev.
38	EMC and Environmental type testing of QWERTY keyboard and cursor control L50 Trackball	2009-3482	1
28	TYPE TESTING OFHM20T07 MIL-E1 Rev. 1 - 2007-3008.pdf		
26	JH19T12MMD-AA1-AAAC Technical Report 2008-3143.pdf		
21	TECDIS conformance test report		3
3	Telko - S63 Loader Manual (User Guide) EN	TELKO S63	1

Tests carried out

- Performance testing: IEC 61174 (2015)*
- Performance testing, presentation: IEC 62288 (2014)*
- Environmental testing: IEC 60945 (2002) incl. Corr. 1 (2008)
- Serial interface testing: IEC 61162-1 (2016)
- Bridge alert management (BAM): IEC 62923-1 (2018) and IEC 62923-2 (2018)

**As amended by NMA RSV-14-22/-16-22*

Marking of product

The Manufacturer and Type Designation to be applied to the equipment in a clearly visible location. In addition, the equipment shall be marked with serial number, safe distance to magnetic compass, power consumption and/or supply voltage.

Periodical assessment

Periodical assessment is to be performed after 2 years and after 3.5 years, alternatively be performed annually together with MED-B/MED-D audit for TECDIS ECDIS.

A renewal assessment will be performed at renewal of the certificate. The scope of the periodical/renewal assessment is to verify that the production quality conditions stipulated for the type approval are complied with and that no alterations are made to the product design or its components and/or materials without appraisal by the Society.