Certificate no.:
TAA00003SM

TYPE APPROVAL CERTIFICATE

This is to certify:

that the Electrical Control System

with type designation(s)
WCD-20

issued to
Altronic LLC
Girard, OH, USA

is found to comply with
DNV rules for classification – Ships, offshore units, and high speed and light craft

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Temperature	**B**
Humidity	**B**
Vibration	**B**
EMC	**A**
Enclosure	**A**

Issued at **Hamburg** on **2025-11-10**
This Certificate is valid until **2030-11-05**.
DNV local unit: **Certification & Inspection Services**

for **DNV**

Approval Engineer: **Jens Dietrich**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

Electric spark ignition system WCD-20 consisting of:

Ignition Controller WCD-20 (Wärtsilä Part Number PAAF649944)
Max. ignition energy: 1000mJ;
Max. number of cylinders per module: 10
Max. engine RPM: 2000,
Input Voltage: 82-140VDC / 110VDC Nominal +/-10%,
Spark voltage: max.40kV / max 47kV in open circuit,
Spark duration: up to 1ms / configurable.

Communication: CANopen, CAN [SAE J1939].

Ignition coils:

Part description	Wärtsilä P/N
IGNITION COIL ISOLATED GROUND, 6m harness, halogen free cable	PABA725677
IGNITION COIL ISOLATED GROUND, 12m harness, halogen free cable	PABA725678

Coil Extensions	Wärtsilä P/N
W600 Extension	PAAF147922
W34SG Extension	PABA567416
W50SG Extension	PAAE186980

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Suitability to be checked for the individual application engine characteristics.

Suitability of Ex-protection is not covered by this certificate and needs to be checked for the respective application.

Product certificate
If specified in the Rules, ref. Pt.4 Ch.9 Sec.1, the control and monitoring system in which the above listed hardware is used shall be delivered with a product certificate. For each such delivery the certification test is to be performed at the manufacturer of the application system before the system is shipped to the yard. The test shall be done according to an approved test program. After certification the clause for software control will be put into force.

Software control
All changes in software are to be recorded as long as the system is in use on board. Documentation of major changes is to be forwarded to DNV for evaluation and approval before implemented on board. Certification of modified functionality may be required for the particular vessel.

Tests carried out

Applicable tests according to DNV CG-0339, August 2021.

Marking of product

WCD-20 Controller: Maker, type designation, Wärtsilä Material number, HW Rev. 10.1, serial number, electrical rating, Ex-rating.
Coil and coil extension: Batch label showing Part number and Mfg. date code, format: YYWW.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.
The main elements of the assessment are:

- Ensure that type approved documentation is available

- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE