

TYPE APPROVAL CERTIFICATE

Certificate No:

TA00000711
DNV GL

This is to certify:

That the Valve

with type designation(s)

3 1/16"-10K Magnum Hyd. F.S. F.E.

Issued to

Worldwide Oilfield Machine, Inc. (WOM)

HOUSTON TX, United States

PUNE, India

is found to comply with

DNV-OS-E101 Drilling Plant October 2013

and DNV GL AS' understanding of the implementation and interpretation of:

PSA's "Regulations relating to design and outfitting of the facilities etc. in the petroleum activities" (THE FACILITIES REGULATIONS), Last amended 16 December 2014, Ch.VIII

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

THIS CERTIFICATE REPLACES D-5886 WHICH EXPIRES JUNE 30TH 2018.

This Certificate is valid until **2018-06-30**.

Issued at **Houston** on **2015-12-08**

for **DNV GL**

DNV GL local station: **Approval CMC – Houston**

Approval Engineer: **Xiangwen (Maggie) Wang**

Christian Nilsen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-017361-3**
Certificate No: **TAD000007J**

Product description

Valve Assy. 3 1/16"-10K Hyd. F.S., P/N: M0406(PH), M3804-NL, M5941, M0040-B(PH) & M1518-B.

Reference standards

- API 6A, 'Specification for Wellhead and Christmas Tree Equipment', 20th Edition
- NACE MR0175/ISO 15156, 'Petroleum and Natural Gas Industries – Material for Use in H₂S – Containing Environments in Oil and Gas Production, 2nd Edition

Application/Limitation

- Max. Working Pressure: 10,000 psi
- Max. Working Pressure (Hyd.): 3,000 psi
- Min. Design Temperature: -20 °F
- Max. Design Temperature: 350 °F
- Service: H₂S
- API 6A Material Class: DD, EE
- API 6A PSL: 3
- API 6A PR: 2

Note: DNV GL surveyor to check materials used in each project for Material Class trim.

Type Approval documentation

Job Id: **262.1-017361-3**
Certificate No: **TAD000007J**

Tests carried out

1. PR-2 Test Certificate for M1251

Marking of product

For traceability the following marking is to be carried out on each product:

1. Serial No.
2. Manufacturer's name or trademark.
3. Marking shall be in accordance with DNV-OS-E101 Ch. 2 Sec.6 1.3 and requirements of API 6A.

Periodical assessment

For retention of the Type Approval, DNV GL's surveyor shall perform a survey every second year in accordance with DNV GL's Class Programme DNVGL-CP-0338, Section 4.

Other conditions/comments

1. Procedures related to testing, welding, NDT, and other quality control requirements are to be reviewed/approved by DNV GL's local surveyor.
2. DNV ref.: Project No. PP095755 199FF/PP124258 222FF

END OF CERTIFICATE