DNV·GL

Certificate No:
TAD00000BJ

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Valve

with type designation(s)
3 1/16"-10K Model 200M Manual Gate

Issued to
Worldwide Oilfield Machine, Inc. (WOM)
HOUSTON TX, United States
PUNE, India

is found to comply with
DNV-OS-E101 Drilling Plant October 2013
DNV-OSS-201 - Verification for Compliance with Norwegian Shelf Regulations - Ch.2 Sec.7 DRILL (N), October 2014

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

THIS CERTIFICATE REPLACES TAC D-5891 WHICH EXPIRES JUNE 30TH 2018
This Certificate is valid until **2018-06-30**.

Issued at **Houston** on **2016-03-21**

for **DNV GL**

DNV GL local station: **Certification & Inspection Services**

Approval Engineer: **Xiangwen (Maggie) Wang**

Christian Nilsen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-017200-3**
Certificate No: **TAD00000BJ**

Product description

- 3 1/16" 10,000 psi WP Model 200M Manual Gate Valve

Reference standards

- API 6A, 'Specification for Wellhead and Christmas Tree Equipment', 20th Edition
- NACE MR0175/ISO 15156, 'Petroleum and Natural Gas Industries – Material for Use in H_2S – Containing Environments in Oil and Gas Production, 2nd Edition

Application/Limitation

- Max. Working Pressure: 10,000 psi
- Min. Design Temperature: -20 °F
- Max. Design Temperature: 350 °F
- Service: H_2S
- API 6A Material Class: DD, EE
- API 6A PSL: 3/3G
- API 6A PR: 2
- Max. Axial Load: 630,000 lbf @ 0 psi, 425,000 lbf @ 10,000 psi for GE4(LMV) ONLY
  Note: DNV GL surveyor to check materials used in each project for Material Class trim.

Type Approval documentation

Tests carried out

1. PR2 report for 2 1/16”-10K Model 200M Manual Gate Valve, P/N: M800M(PH) (Temp. -20F to 350 F), S/N: PR2-6185

Marking of product

For traceability the following marking is to be carried out on each product:

1. Serial No.
2. Manufacturer’s name or trademark.
3. Marking shall be in accordance with DNV-OS-E101 Ch. 2 Sec.6 and requirements of API 6A.

Periodical assessment

For retention of the Type Approval, DNV GL’s surveyor shall perform a survey every second year in accordance with DNV GL’s Class Programme DNVGL-CP-0338, 2015 edition

Other conditions/comments

1. Procedures related to testing, welding, NDT, and other quality control requirements are to be reviewed/approved by DNV GL’s local surveyor.
2. DNV GL ref.: Project No. PP095755-181FF/PP150835-024FF

END OF CERTIFICATE