

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Mud and Cementing Equipment**

with type designation(s)

PCSE-621A Double Cementing Pump Skid, Model B01-00-300

Issued to

SJS Limited**Jingzhou City, Hubei, China**

is found to comply with

DNVGL-OS-E101 – Drilling facilities, Edition January 2018

Application :**See Page 2**Issued at **Houston** on **2018-11-02**This Certificate is valid until **2023-11-01**.DNV GL local station: **Wuhan CMC**for **DNV GL**Approval Engineer: **M. Kevin Mandeville Jr.**

Meindert van Mierlo
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-024456-1**
Certificate No: **TAD00000ME**

The following codes and standards were used as a reference:

API Specification 7K, *Specification for Drilling and Well Servicing Equipment*, 5th Edition

Product description

PCSE-621A Double Pump Cementing Skid.

Application/Limitation

Design Parameter	Value	Equivalent
Minimum Working Temperature	-20°C	-4°F
Maximum Working Temperature	50°C	122°F
Maximum Pressure (High Pressure Side)	105 MPa	15,000 psi
Hydraulic System Pressure Rating	28 MPa	4,000 psi
High Pressure Manifold Parts PSL	3	
High Pressure Manifold Parts PR	1	
Area Classification	Zone II	
Accelerations		
Transverse	≤3.0m/s ²	
Longitudinal	≤3.0m/s ²	
Vertical	≤5.0m/s ²	

Type Approval documentation



Job Id: **262.1-024456-1**
Certificate No: **TAD00000ME**

Marking of product

For traceability, the following marking is to be carried out on each product:

1. Serial Number
2. Manufacturer's name or trademark
3. Additional Marking at the manufacturer's discretion

Certificate Retention Survey

For retention of the Type Approval Certificate, DNV GL's surveyor shall perform a survey every second year in accordance with DNV GL's Class Programme for Type Approval, DNVGL-CP-0338.

Job Id: **262.1-024456-1**
Certificate No: **TAD00000ME**

Other Comments and Conditions

1. The pump fluid ends are to be provided with their own product certificate, and the design is certified under Type Approval Certificate D-6109. Other Category I items not named in the drawing section above, such as electric motors, should also be purchased with a product certificate already issued by DNV GL.
2. Skid frame is reviewed for installation lift only.
3. Scope of certificate does not include flexible cement hoses for discharge.
4. Skid can be used in emergency well kill operations, provided the skid remains in a Zone II hazardous area. Per DNVGL-OS-E101, Chapter 2, Section 5, Part 7.3.7, facilities for transferring mud to the cementing system shall be provided.
5. HAZLOC Ex documentation (where applicable) shall be submitted to DNV GL surveyor at site. For EX certificates with certificate number that is ending with 'U' or 'X', a document stating compliance with the special conditions given in the certificate shall be presented and demonstrated to local DNV GL Surveyor.
6. The Category II items shall be delivered with a works certificate prepared by the manufacturer.
7. The EX J-box explosion proof certificate shall be reviewed and accepted by the local DNVGL Surveyor prior to certification.
8. Factory Acceptance Testing of the completed skid must be completed and witnessed by a DNV GL surveyor prior to the issuance of a Product Certificate.

END OF CERTIFICATE