



Certificate No:
TAD00001EZ

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Kill and Choke Equipment

with type designation(s)
3-1/16" 15K 2.0 Trim HXE-G3 Choke

Issued to

**National Oilwell Varco, L.P. - Rig Technologies Division - Creekmont
Houston, TX, USA**

is found to comply with

DNV-OS-E101 – Drilling facilities, Edition July 2021

DNVGL-SI-0166 – Verification for compliance with Norwegian shelf regulations, Edition July 2018

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

See "Other conditions/comments" on page 4 regarding the validity.

Issued at **Houston** on **2021-08-13**

This Certificate is valid until **2021-09-30**.

for **DNV**

DNV local station: **Houston, Approval CMC**

Approval Engineer: **Xiangwen Maggie Wang**

.....
Mark Miser
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2021-03

www.dnv.com

Page 1 of 2

Product description

- 3-1/16" 15K HXE-G3 Hydraulic Piston Operated Choke, Part No. 20407364 (10295581-001), 10295581-002
- 3-1/16" 15K HXE-G3 Manual Choke, Part No. 10301179-003, 10301179-014
- 3-1/16" 15K HXE-G3 Hydraulic Gear Operated Choke, Part No. 10300231-013

Reference standards

- API 6A, Specification for Wellhead and Tree Equipment, 21st Edition
- API 16C, Choke and Kill Equipment, 2nd Edition
- NACE MR0175/ISO 15156, 'Petroleum and Natural Gas Industries – Materials for Use in H₂S – Containing Environments in Oil and Gas Production', 3rd Edition

Application/Limitation

- Max. Working Pressure: 15,000 psi
- Test Pressure: 22,500 psi
- Design Temperature: -50 °F to 350 °F
- Max. Working Pressure (Actuator): 2,500 psi
- Test Pressure (Actuator): 3,750 psi
- Design Temperature (Actuator): -50 °F to 150 °F
- Service: H₂S
- Material Class: EE-508 (P/N: 20407364); EE
- Product Specification Level: 3
- Performance Requirement: API 6A PR2F; API 16C

Type Approval documentation

Drawings:

Tests carried out

Doc. No. SwRI 18.18125.01.037, API Spec 16C Sec 9, 3-1/16 15K 2.0 Trim HXE-G3 Hydraulic Choke
P/N 102-1202-40, S/N RD1900C7-1-1, dated Aug. 2020

Marking of product

For traceability the following marking is to be carried out on each product:

1. Serial No.
2. Manufacturer's name or trademark.
3. Additional Marking at manufacturer's discretion.

Periodical assessment

For retention of the Type Approval, DNV's surveyor shall perform periodical assessment after 2.5 years in accordance with DNV's Class Programme DNVGL-CP-0338.

Other conditions/comments

1. Procedures related to testing, welding, NDT, and other quality control requirements are to be reviewed/approved by DNV's local surveyor.
2. DNV ref.: A1068298.
3. This Certificate is a renewal of D-5157 with additional approved assemblies. After 30th Sept. 2021, a revision will be issued to reference the 3rd edition of API 16C when updated documentation is received. The total validity of the Certificate will remain 5 years until next renewal.

END OF CERTIFICATE