DNV·GL

Certificate No:
TAE00000SM

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Cable Tray

with type designation(s)
MCL

Issued to
Ackron International Manufacturing (M) Sdn Bhd
Johor, Malaysia

is found to comply with
DNV GL rules for classification – Ships and offshore units

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

This Certificate is valid until **2021-06-14**.

Issued at **Høvik** on **2016-06-15**

for **DNV GL**

DNV GL local station: **Certification of Materials - Singapore**

Approval Engineer: **Ivar Bull**

Marit Laumann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-020787-1**
Certificate No: **TAE00000SM**

Product description

Cable ladder	
Type	MCL
RFSR	Return Flange Side Rail
Material/Finishing	Mild steel (MS), Stainless Steel 316L (SUS316L) / Hot Dipped Galvanized (HDG)

No.	Model	Material/ Finishing	W mm	H mm	Rung type	T mm	L mm	CSA Class des. kg/m	SWL kg/m
1	MCL	(MS) HDG	1000	100	B	2	3000	"E" 299	333.41
2	MCL	SUS316L	1000	100	B	2	3000	"E" 299	333.41
3	MCL	(MS) HDG	900	100	B	2	3000	"E" 299	333.41
4	MCL	SUS316L	900	100	B	2	3000	"E" 299	333.41
5	MCL	(MS) HDG	1000	100	B	1,5	3000	"E" 299	333.41
6	MCL	SUS316L	1000	100	B	1,5	3000	"E" 299	306.74
7	MCL	(MS) HDG	900	100	B	1,5	3000	"E" 299	333.41
8	MCL	SUS316L	900	100	B	1,5	3000	"E" 299	320.08
9	MCL	(MS) HDG	1000	75	B	2	3000	"E" 299	333.41
10	MCL	SUS316L	1000	75	B	2	3000	"E" 299	333.41
11	MCL	(MS) HDG	900	75	B	2	3000	"E" 299	333.41
12	MCL	SUS316L	900	75	B	2	3000	"E" 299	333.41
13	MCL	(MS) HDG	1000	75	B	1,5	3000	"D" 179	272.74
14	MCL	SUS316L	1000	75	B	1,5	3000	"D" 179	272.74
15	MCL	(MS) HDG	900	75	B	1,5	3000	"D" 179	272.74
16	MCL	SUS316L	900	75	B	1,5	3000	"D" 179	272.74
17	MCL	(MS) HDG	1000	50	B	2	3000	"D" 179	194.74
18	MCL	SUS316L	1000	50	B	2	3000	"D" 179	216.08
19	MCL	(MS) HDG	900	50	B	2	3000	"D" 179	189.41
20	MCL	SUS316L	900	50	B	2	3000	"D" 179	212.74
21	MCL	(MS) HDG	1000	50	B	1,5	3000	"C" 97	136.08
22	MCL	SUS316L	1000	50	B	1,5	3000	"C" 97	136.08
23	MCL	(MS) HDG	900	50	B	1,5	3000	"C" 97	136.08
24	MCL	SUS316L	900	50	B	1,5	3000	"C" 97	152.74

Application/Limitation

The installation is to be mechanically protected in accordance with DNV Rules and especially on weather decks in cargo hold areas and through cargo holds.
Cable ladders must not to be used as a walkway.

Type Approval documentation

Tests carried out

Tested in accordance with IEC 61537 Impact resistance test, Electrical properties, Resistance to corrosion, Safe Working Load (SWL) and in accordance with NEMA VE 1-2009 and CSA C22.2 No.126.1-09, loading material, Load application, loading to destruction (Method A)

Marking of product

Ackron International Manufacturing – Type designation – Type – Width – Height – Length.

Periodical assessment

The scope of the periodical assessments to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the periodical assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routines (RT) checked (if not available tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment to be performed at least every second year.

END OF CERTIFICATE