

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Electric Power Cable

with type designation(s)
EXANE-MR, 125 Type P, BH, Armor & Sheath (A&S)

Issued to

RSCC Wire & Cable LLC
East Granby CT, United States

is found to comply with
DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Instrumentation and communication.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Voltage class (kV) 1 & 2 & 2kVHD

Temp. class (°C) 95

Issued at **Høvik** on **2017-05-30**

This Certificate is valid until **2021-06-30**.

DNV GL local station: **New York**

for **DNV GL**

Approval Engineer: **Ivar Bull**

.....
Andreas Kristoffersen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-007169-4**
Certificate No: **TAE000012Y**

Product description

Construction: Exane-MR, Exane 125 Type P, BH, Armor & Sheath
Conductor: Stranded tinned copper
Insulation: XLPO (type P)
Shields: Individual shield (IS) and /or overall shield (OS) aluminium mylar with drain wire or tinned copper braid (OBS). Pairs (P) & Triads (T) & Conductors (C).
Filler: Flame retardant (as required)
Armor: C = Tinned Copper Braid; B = Bronze Braid; S = Stainless Steel Braid
Sheath: SH (type CP or CPE); Reference = H

No of elements	mm²	AWG range	Type Designation (example)
1 core	7,6*	8	Exane-MR-1C8-BH-1kV
	12,5	6	Exane-MR-1C8-BH-2kV
	18,6	5	
	21,5	4	
	25,8	3	
	30,7	2	
	46,3	1	
	56,5	1/0	
	66,1	2/0	
	92,9	3/0	
	113	4/0	
	133	262	
	159	313	
	189	373	
	225	444	
	271	535	
	303	600	
	328	646	
	394	777	
	563	1111	
1core	113	4/0	Exane-MR-1C4/0-BH-2kV HD
	133	262	
	159	313	
	189	373	
	225	444	
	271	535	
	303	600	
	328	646	
	394	777	
	563	1111	
Multiconductors:			
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91	0,96	18	Exane-MR-2C18-BH-1KV
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91	1,23	16	
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44	1,94	14	
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44	3,08	12	
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37	5,53	10	
2,3,4,5	7,6	8	
2,3,4,5	12,5	6	
2,3,4,5	18,6	5	
2,3,4,5	21,5	4	
2,3,4,5	25,8	3	
2,3,4,5	30,7	2	
2,3,4,5	46,3	1	
2,3,4,5	56,5	1/0	
2,3,4,5	66,1	2/0	
2,3,4,5	92,9	3/0	
2,3,4,5	113	4/0	
2,3,4,5	133	262	
2,3,4	159	313	

Job Id: **262.1-007169-4**
 Certificate No: **TAE000012Y**

2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4	189 225 271 303 328 394	373 444 535 600 646 777	
2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4	12,5 18,6 21,5 25,8 30,7 46,3 56,5 66,1 92,9 113 133 159 189 225 271 303 328 394	6 5 4 3 2 1 1/0 2/0 3/0 4/0 262 313 373 444 535 600 646 777	Exane-MR-2C18-BH- 2KV
2,3,4,5 2,3,4,5 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37	113 133 159 189 225 271 303 328 394	4/0 262 313 373 444 535 600 646 777	Exane-MR-1C4/0-BH-2kV HD
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37	0,96 1,23 1,94 3,08 5,53	18 16 14 12 10	Exane-MR-2C20- OS -BH-1kV
2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44,60,91 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37,44 2,3,4,5,6,7,8,9,10,11,12,14,16,18,19,20,22,24,26,30,37 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3 2,3,4,5 2,3,4,5	0,96 1,23 1,94 3,08 5,53 7,6 12,5 18,6 21,5 25,8 30,7 46,3 56,5 66,1 92,9 113 133 159 189 225 271 303 328 394	18 16 14 12 10 8 6 5 4 3 2 1 1/0 2/0 3/0 4/0 262 313 373 444 535 600 646 777	Exane-MR-2C20- OBS -BH-1kV
2,3,4,5 2,3,4,5	12,5 18,6	6 5	Exane-MR-2C20- OBS -

Job Id: **262.1-007169-4**
Certificate No: **TAE000012Y**

2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4,5 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3	21,5 25,8 30,7 46,3 56,5 66,1 92,9 113 133 159 189 225 271 303 328 394	4 3 2 1 1/0 2/0 3/0 4/0 262 313 373 444 535 600 646 777	BH-2kV (from 12,5 mm ²)
2,3,4,5 2,3,4,5 2,3,4,5 2,3,4 2,3,4 2,3,4 2,3,4 2,3,4 2,3	113 133 159 189 225 271 303 328 394	4/0 262 313 373 444 535 600 646 777	Exane-MR-1C4/0- OBS - 2kV HD
1,2,3,4,5,6,7,8,9,10,12,14,16,18,19,20,22,24,30,36 PAIRS	0,96 1,23 1,94 3,08 5,53	18 16 14 12 10	Exane-MR-1P20- OS -BH- 1KV Exane-MR-1P20- ISOS - BH-1KV Exane-MR-1P20- IS -BH- 1KV Exane-MR-1P20- OBS - BH-1KV
1,2,3,4,5,6,7,8,9,10,12,14,16,18,19,20,22,24 TRIPLES	0,96 1,23 1,94 3,08 5,53	18 16 14 12 10	Exane-MR-1P20- OS -BH- 1KV Exane-MR-1P20- ISOS - BH-1KV Exane-MR-1P20- IS -BH- 1KV

Application/Limitation

The cable may be installed and sized according to IEC 60092-352 provided Cable ends with flexible rope stranded conductors are to be terminated using approved compression terminals intended and designed for these conductors.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Job Id: **262.1-007169-4**
Certificate No: **TAE000012Y**

Tests carried out

Standard	Issued	General description	Limitation
IEEE1580	2010	IEEE Recommended Practice for Marine Cable for Use on Shipboard and Fixed or Floating Facilities	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
NEK 606 Ed. 4	2009	Cables for offshore installations. Halogen-free and/or mud resistant. Technical specification.	Mud resistance test: IRM903 100°C 7d. Calcium Bromide 70°C 56d. <u>Oil based mud:</u> EDC 95-11 70°C 56d or EDC 95/11 70°C 56d

Marking of product

EXANE –MR Type P - IEEE1580 - Type designation - number and size of conductors – Voltage- IEC 60332-3-22 – Year

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE