

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Low Voltage Cable**with type designation(s)
BFOU (C) & BFOU (I) 250 V

Issued to

Nexans (Suzhou) Cable Solutions Co.,Ltd
Suzhou Jiangsu, China

is found to comply with

DNV GL rules for classification – Ships**DNV GL offshore standards****DNV GL rules for classification – High speed and light craft****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Voltage class (V) 250****Temp. class (°C) 90**This Certificate is valid until **2017-06-30**.Issued at **Hamburg** on **2016-08-08**DNV GL local station: **Shanghai CMC**for **DNV GL**Approval Engineer: **Carsten Hunsalz**

Duy Nam Le
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Product description

Type: BFOU (C) & (I) 250 V

Construction:

Conductors: Tinned stranded copper class 2
Core insulation: Mica tape + XLPE
Screen: Cu/PET tape w/tinned copper drain wire
Inner covering: SHF1
Metal covering: Tinned copper wire braid
Outer sheath: SHF2

Number of cores x conductor cross-section mm ²	Overall Diameter min (I) mm	Overall Diameter max (I) mm	Overall Diameter min (C) mm	Overall Diameter max (C) mm
1 x 2 x 0,5	10,5	12,5	10,0	12,0
2 x 2 x 0,5	15,5	17,5	11,5	13,0
3 x 2 x 0,5	16,5	19,0	14,5	16,5
4 x 2 x 0,5	18,0	20,5	16,5	19,0
5 x 2 x 0,5	19,5	22,0	17,5	20,0
7 x 2 x 0,5	20,5	23,5	19,5	22,0
10 x 2 x 0,5	23,5	26,5	22,5	25,0
12 x 2 x 0,5	25,0	28,0	23,5	26,0
14 x 2 x 0,5	25,5	28,5	24,5	27,5
19 x 2 x 0,5	30,5	34,0	28,5	32,0
24 x 2 x 0,5	34,0	37,5	31,5	35,0
27 x 2 x 0,5	35,5	39,5	33,0	37,0
30 x 2 x 0,5	38,0	42,0	35,0	38,5
37 x 2 x 0,5	41,5	45,5	38,5	42,5
1 x 2 x 0,75	11,0	12,5	10,5	12,5
2 x 2 x 0,75	16,5	18,5	12,0	14,0
3 x 2 x 0,75	17,0	19,0	16,0	18,0
4 x 2 x 0,75	18,5	21,0	17,5	19,5
5 x 2 x 0,75	20,0	22,5	18,5	21,0
7 x 2 x 0,75	21,5	24,5	20,5	23,0
10 x 2 x 0,75	24,5	27,5	24,0	27,0
12 x 2 x 0,75	26,0	29,0	25,5	28,5
14 x 2 x 0,75	27,0	30,0	26,5	29,5
19 x 2 x 0,75	32,0	35,5	30,0	33,5
24 x 2 x 0,75	36,0	40,0	33,5	37,5
27 x 2 x 0,75	38,0	42,0	35,0	39,0
30 x 2 x 0,75	40,0	44,0	37,5	41,5
37 x 2 x 0,75	44,0	48,5	41,0	45,0
1 x 2 x 1,0	11,5	13,0	11,0	13,0
2 x 2 x 1,0	16,5	19,0	12,5	14,5
3 x 2 x 1,0	17,5	19,5	16,5	19,0
4 x 2 x 1,0	19,0	21,5	18,0	20,5
5 x 2 x 1,0	20,5	23,0	19,5	22,0
7 x 2 x 1,0	22,5	25,0	21,5	24,0
10 x 2 x 1,0	26,0	29,0	25,0	28,0

Job Id:
Certificate No: **TAE00001AW**

Number of cores x conductor cross-section mm ²	Overall Diameter min (I) mm	Overall Diameter max (I) mm	Overall Diameter min (C) mm	Overall Diameter max (C) mm
12 x 2 x 1,0	27,0	30,5	26,5	30,0
14 x 2 x 1,0	28,0	31,5	28,0	31,5
19 x 2 x 1,0	33,5	37,0	32,0	35,5
24 x 2 x 1,0	37,5	41,5	35,5	39,0
27 x 2 x 1,0	39,5	44,0	37,5	41,5
30 x 2 x 1,0	42,0	46,5	39,5	43,5
37 x 2 x 1,0	46,0	50,5	43,5	48,0
1 x 2 x 1,5	12,0	14,0	11,5	13,5
2 x 2 x 1,5	14,0	16,0	13,0	15,0
3 x 2 x 1,5	18,0	20,5	17,5	19,5
4 x 2 x 1,5	20,0	22,5	19,0	21,5
5 x 2 x 1,5	21,0	24,0	20,5	23,0
7 x 2 x 1,5	23,5	26,5	22,5	25,5
10 x 2 x 1,5	27,5	31,0	26,5	29,5
12 x 2 x 1,5	29,5	32,5	28,5	31,5
14 x 2 x 1,5	31,0	34,5	29,5	33,0
19 x 2 x 1,5	35,5	39,5	34,0	37,5
24 x 2 x 1,5	40,0	44,5	38,5	43,0
27 x 2 x 1,5	42,0	46,5	40,5	45,0
30 x 2 x 1,5	44,0	48,5	42,5	47,0
37 x 2 x 1,5	48,5	53,5	46,5	51,5
1 x 2 x 2,5	13,0	15,0	12,5	14,5
2 x 2 x 2,5	15,5	17,5	15,0	17,0
3 x 2 x 2,5	-	-	19,0	21,5
4 x 2 x 2,5	21,5	24,5	21,0	24,0
5 x 2 x 2,5	23,5	26,5	22,5	25,5
7 x 2 x 2,5	26,0	29,0	25,0	28,0
10 x 2 x 2,5	30,5	34,0	29,5	33,0
12 x 2 x 2,5	33,5	37,0	32,0	35,5
14 x 2 x 2,5	35,0	38,5	33,5	37,0
1 x 3 x 0,5	11,0	13,0	10,5	12,5
2 x 3 x 0,5	16,5	19,0	16,0	18,0
3 x 3 x 0,5	17,5	20,0	16,5	19,0
4 x 3 x 0,5	19,0	21,5	18,0	20,0
7 x 3 x 0,5	23,5	26,0	22,0	25,0
10 x 3 x 0,5	27,0	30,0	25,5	28,5
14 x 3 x 0,5	30,5	34,0	29,0	32,5
1 x 3 x 0,75	11,5	13,0	11,0	13,0
2 x 3 x 0,75	17,0	19,5	16,5	19,0
3 x 3 x 0,75	18,5	20,5	17,5	19,5
4 x 3 x 0,75	20,0	22,5	19,0	21,5
7 x 3 x 0,75	24,5	27,0	23,5	26,5
10 x 3 x 0,75	28,0	31,0	27,0	30,0
14 x 3 x 0,75	32,0	35,5	31,0	34,5

Number of cores x conductor cross-section mm ²	Overall Diameter min (I) mm	Overall Diameter max (I) mm	Overall Diameter min (C) mm	Overall Diameter max (C) mm
1 x 3 x 1,0	11,5	13,5	11,5	13,5
2 x 3 x 1,0	18,0	20,0	17,5	19,5
4 x 3 x 1,0	20,5	23,0	20,0	22,5
1 x 3 x 1,5	12,5	14,5	12,0	14,0
2 x 3 x 1,5	18,5	21,0	18,0	20,5
4 x 3 x 1,5	21,5	24,0	21,0	23,5
1 x 3 x 2,5	13,5	15,5	13,0	15,0

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publication 60331.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Control and instrumentation. Halogen free. Low smoke.

Type Approval documentation

Tests carried out

Standard	Issued	General description	Limitation
IEC 60092-350	2008-02	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-351	2004-04	Insulating materials for shipboard and offshore units, power, control, instrumentation, telecommunication and data cables	
IEC 60092-376	2003-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60092-359	1999-08	Sheathing materials for shipboard power and telecommunication cables	
IEC 60331-21	1999-04	Tests for electric cables under fire conditions Circuit integrity Part 21: Procedures and requirements. Cables of rated voltage up to and including 0,6/1,0 kV	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen: <0,5% Halogen
IEC 61034-2	2005-04	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke



Job Id:
Certificate No: **TAE00001AW**

Marking of product

Product marking: NEXANS 448 – BFOU (C) or BFOU (I) - size – 250 V

Periodical assessment

The scope of the Periodical assessment is to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the survey are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routines (RT) checked (if not available tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Survey to be performed at least every second year.

END OF CERTIFICATE