

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Electric Power Cable**with type designation(s)
TXOI EMC 0,6/1 kV

Issued to

Suzhou Draka Cable Co. Ltd.
SUZHOU JIANGSU, China

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Voltage class (kV) 0,6/1****Temp. class (°C) 90**Issued at **Hamburg** on **2017-05-12**This Certificate is valid until **2022-05-11**.DNV GL local station: **Shanghai**for **DNV GL**Approval Engineer: **Holger Jansen**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Type: TXOI EMC 0,6/1 kV

Conductors: Plain or Tinned, stranded copper
Core insulation: XLPE
Earth conductors (if any): 3x distributed earth conductors in interstics
Inner covering: Polyester tape
Screen: Cu-PET tape
Metal covering: Plain copper wire braid
Outer sheath: SHF1

Number of cores x conductor cross-section*	Overall diameter Nominal
mm ²	mm
3 x 1,5	10,1
3 x 2,5	11,0
3 x 4	12,3
3 x 6	13,5
3 x 10	16,2
3 x 16	19,1
3 x 25	23,0
3 x 35	25,6
3 x 50	29,5
3 x 70	34,9
3 x 95	39,4
3 x 120	44,3
3 x 150	48,0

Number of cores x conductor cross-section*	Overall diameter Nominal
mm ²	mm
4 x 1,5	10,5
4 x 2,5	12,0
4 x 4	13,3
4 x 6	15,3
4 x 10	17,7
4 x 16	21,0
4 x 25	25,3
4 x 35	28,4
4 x 50	32,6
4 x 70	38,4
4 x 95	44,1
4 x 120	48,9

Number of cores x conductor cross-section*	Overall diameter Nominal
mm ²	mm
3 x 70+ 3 x 16	34,9
3 x 95+ 3 x 16	39,4
3 x 120+ 3 x 25	44,3
3 x 150+ 3 x 25	48,0

* Sector shaped

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

General power and lighting. Control. Halogen free. Low smoke. Flame retardant in bunch Cat. A.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-353	2016-09	Single and multicore non-radial field power cables with extruded solid insulation for rated Voltages of 1 kV and 3 kV	

Job Id: **262.1-013242-2**
Certificate No: **TAE00001YJ**

Standard	Release	General description	Limitation
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	
IEC 61034-1/2	2013-06	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	

Marking of product

Draka 83 – TXOI EMC – 0,6/1 kV – 90°C – Size – IEC 60332-3-22 – Lot no.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE