

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Electric Power Cable**with type designation(s)  
**P1 & P1/P8 RFOU 0,6/1 kV**

Issued to

**Changzhou Marine Cable Co., Ltd. (CMC)**  
**CHANGZHOU JIANGSU, China**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****General power and lighting. Control.****Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.****Rated voltage (kV) 0,6/1**  
**Temp. class (°C) 90**Issued at **Høvik** on **2017-11-06**This Certificate is valid until **2022-06-30**.for **DNV GL**DNV GL local station: **Shanghai**Approval Engineer: **Marta Alonso Pontes**

---

**Andreas Kristoffersen**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-007592-4**  
Certificate No: **TAE0000248**

## Product description

Type: P1 & P1/P8 RFOU 0,6/1 kV

Conductors: Tinned stranded copper class 2  
Core insulation: EPR  
Inner covering: Halogen free compound  
Metal covering: Tinned copper wire braid  
Outer sheath: SHF2 or SHF Mud

| Number of conductors                         | Conductor cross section [mm <sup>2</sup> ]                                                                 |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------|
| 1                                            | 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300                                                            |
| 2                                            | 1.5, 2.5, 4, 6, 10, 16                                                                                     |
| 3                                            | 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185                                                  |
| 4                                            | 1.5/G1.5, 2.5/G2.5, 4/G4, 6/G6, 10/G10, 16/G16, 25/G25, 35/G35, 50/G50, 70/G70, 95/G95, 120/G120, 150/G150 |
| 5, 7, 10, 12, 14, 16, 19, 24, 27, 30, 33, 37 | 1.5, 2.5                                                                                                   |

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

## Type Approval documentation

### Tests carried out

| Standard       | Release            | General description                                                                                                                                                     | Limitation                                                                                                                    |
|----------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| IEC 60092-353  | 2016-09            | Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV                                                                             |                                                                                                                               |
| IEC 60332-3-22 | 2009-02            | Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A | Charred portion of sample does not exceed 2,5m above bottom edge of burner.                                                   |
| IEC 60754-1    | 2011-11            | Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content                                                | Low Halogen: <0,5% Halogen                                                                                                    |
| IEC 60754-2    | 2011-11            | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity                                | Halogen free: pH > 4,3<br>Conductivity < 10µS/mm                                                                              |
| IEC 61034-1/2  | 2013-07<br>2013-09 | Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements                                                    | Low smoke<br>Light transmittance ≥60%                                                                                         |
| NEK 606 Ed.4   | 2009-05            | Cables for offshore installations. Halogenfree and/or mud resistant. Technical specification.                                                                           | Mud resistance test: IRM903 100°C 7d.<br>Calcium Bromide 70°C 56d.<br>Oil based mud: Carbo Sea 70°C 56d or EDC 95/11 70°C 56d |

Job Id: **262.1-007592-4**  
Certificate No: **TAE0000248**

### **Marking of product**

CMCW – P1 or P1/P8 RFOU - 0,6/1 kV – size – IEC 60332-3-22 – Lot No.

### **Periodical assessment**

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE