

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Low Voltage Cable

with type designation(s)
CHEH92

Issued to

Hebei Huatong Wires & Cables Group Co., Ltd.
Tangshan, China

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Rated voltage (V) 150/250

Temp. class (°C) 90

Issued at **Hamburg** on **2017-08-10**

This Certificate is valid until **2022-08-09**.

DNV GL local station: **Tianjin**

for **DNV GL**

Approval Engineer: **Carsten Hunsalz**

.....
Duy Nam Le
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-008108-15**
Certificate No: **TAE000026F**

Product description

Type: CHEH92 150/250 V

Construction:
Conductors: Plain or tinned stranded copper
Core insulation: EPR
Inner sheath: SHF2
Metal covering: Galv. steel wire braid
Outer sheath: SHF2

Number of cores x conductor cross-section mm ²	Overall Dia- meter min. mm	Overall Dia- meter max. mm
2 x 0,5	8,4	10,0
3 x 0,5	8,8	10,5
4 x 0,5	9,4	11,0
5 x 0,5	9,8	12,0
6 x 0,5	10,5	12,5
7 x 0,5	10,5	12,5
8 x 0,5	11,0	13,5
10 x 0,5	13,0	15,5
12 x 0,5	13,5	16,0
14 x 0,5	14,0	17,0
16 x 0,5	14,0	17,0
19 x 0,5	15,5	18,5
24 x 0,5	18,0	21,0
27 x 0,5	18,0	21,0
30 x 0,5	18,5	22,0
37 x 0,5	20,0	23,5
2 x 0,75	8,8	10,5
3 x 0,75	9,2	11,0
4 x 0,75	9,8	11,5
5 x 0,75	10,5	12,5
6 x 0,75	11,0	13,5
7 x 0,75	11,0	13,5
8 x 0,75	12,0	14,5
10 x 0,75	14,0	17,0
12 x 0,75	14,5	17,0
14 x 0,75	15,0	18,0
16 x 0,75	15,0	18,0
19 x 0,75	16,5	19,5
24 x 0,75	19,0	22,0
27 x 0,75	19,5	22,5
30 x 0,75	20,0	23,5
37 x 0,75	21,5	25,0
2 x 1,0	9,0	11,0
3 x 1,0	9,4	11,5
4 x 1,0	10,0	12,0
5 x 1,0	10,5	13,0
6 x 1,0	11,5	14,0
7 x 1,0	11,5	14,0
8 x 1,0	12,5	15,0

Number of cores x conductor cross-section mm ²	Overall Dia- meter min. mm	Overall Dia- meter max. mm
10 x 1,0	14,5	17,5
12 x 1,0	15,0	18,0
14 x 1,0	15,5	19,0
16 x 1,0	15,5	19,0
19 x 1,0	17,0	20,5
24 x 1,0	20,0	24,0
27 x 1,0	20,0	24,0
30 x 1,0	21,0	25,0
37 x 1,0	22,5	26,5
2 x 1,5	10,0	12,0
3 x 1,5	10,5	12,5
4 x 1,5	11,5	14,0
5 x 1,5	12,0	15,0
6 x 1,5	13,5	16,5
7 x 1,5	13,5	16,5
8 x 1,5	14,5	17,5
10 x 1,5	17,0	20,0
12 x 1,5	17,4	20,5
14 x 1,5	18,0	21,5
16 x 1,5	18,0	21,5
19 x 1,5	20,0	24,0
24 x 1,5	23,0	27,0
27 x 1,5	23,5	27,5
30 x 1,5	24,5	28,5
37 x 1,5	26,0	31,0
2 x 2,5	11,0	13,5
3 x 2,5	11,5	14,0
4 x 2,5	13,0	15,5
5 x 2,5	14,0	17,0
6 x 2,5	15,0	18,0
7 x 2,5	15,0	18,0
8 x 2,5	16,0	19,0
10 x 2,5	18,5	22,0
12 x 2,5	19,0	22,5
14 x 2,5	20,0	24,0
16 x 2,5	20,0	24,0
19 x 2,5	22,0	26,0
24 x 2,5	26,0	30,5
27 x 2,5	26,5	31,0

Job Id: **262.1-008108-15**
 Certificate No: **TAE000026F**

30 x 2,5	27,0	32,0
37 x 2,5	29,5	34,5
2 x 2 x 0,5	11,5	14,0
3 x 2 x 0,5	12,0	14,5
4 x 2 x 0,5	13,5	16,0
5 x 2 x 0,5	14,5	17,5
6 x 2 x 0,5	16,0	18,5
7 x 2 x 0,5	16,0	18,5
8 x 2 x 0,5	17,0	20,0
10 x 2 x 0,5	20,0	23,0
12 x 2 x 0,5	20,5	23,5
14 x 2 x 0,5	21,0	24,5
16 x 2 x 0,5	21,0	24,5
19 x 2 x 0,5	23,5	27,0
24 x 2 x 0,5	27,0	31,5
27 x 2 x 0,5	27,5	32,0
30 x 2 x 0,5	29,0	33,5
37 x 2 x 0,5	31,0	36,0
2 x 2 x 0,75	12,0	14,5
3 x 2 x 0,75	13,0	15,5
4 x 2 x 0,75	14,5	17,0
5 x 2 x 0,75	15,5	18,5
6 x 2 x 0,75	17,0	20,0
7 x 2 x 0,75	17,0	20,0
8 x 2 x 0,75	18,0	21,0
10 x 2 x 0,75	21,0	24,5
12 x 2 x 0,75	21,5	25,0
14 x 2 x 0,75	23,0	26,5
16 x 2 x 0,75	23,0	26,5
19 x 2 x 0,75	25,5	29,5
24 x 2 x 0,75	29,5	34,0
27 x 2 x 0,75	30,0	34,5
30 x 2 x 0,75	31,0	36,0
37 x 2 x 0,75	34,5	39,5
2 x 2 x 1,0	13,0	16,0
3 x 2 x 1,0	13,5	16,5
4 x 2 x 1,0	15,0	18,0
5 x 2 x 1,0	16,0	19,5
6 x 2 x 1,0	17,5	21,0
7 x 2 x 1,0	17,5	21,0
8 x 2 x 1,0	18,5	22,5
10 x 2 x 1,0	21,5	26,0
12 x 2 x 1,0	22,5	27,0
14 x 2 x 1,0	23,5	28,0
16 x 2 x 1,0	25,0	29,5
19 x 2 x 1,0	26,0	31,0
24 x 2 x 1,0	30,5	36,0
27 x 2 x 1,0	31,0	37,0
30 x 2 x 1,0	32,5	38,5
37 x 2 x 1,0	35,5	42,0
2 x 2 x 1,5	15,0	17,5
3 x 2 x 1,5	15,5	18,5
4 x 2 x 1,5	17,0	20,5
5 x 2 x 1,5	18,5	22,0

6 x 2 x 1,5	20,0	24,0
7 x 2 x 1,5	20,0	24,0
8 x 2 x 1,5	21,5	25,5
10 x 2 x 1,5	25,5	30,0
12 x 2 x 1,5	26,0	31,0
14 x 2 x 1,5	27,5	32,0
16 x 2 x 1,5	29,0	34,0
19 x 2 x 1,5	30,5	36,0
24 x 2 x 1,5	36,5	43,0
27 x 2 x 1,5	37,5	44,0
30 x 2 x 1,5	39,0	45,0
37 x 2 x 1,5	42,0	49,0
2 x 2 x 2,5	16,5	19,5
3 x 2 x 2,5	17,5	20,5
4 x 2 x 2,5	18,5	22,0
5 x 2 x 2,5	20,5	24,5
6 x 2 x 2,5	22,5	26,5
7 x 2 x 2,5	22,5	26,5
8 x 2 x 2,5	24,0	28,5
10 x 2 x 2,5	28,5	33,5
12 x 2 x 2,5	29,5	34,5
14 x 2 x 2,5	31,0	36,0
16 x 2 x 2,5	32,5	38,0
19 x 2 x 2,5	35,0	41,0
24 x 2 x 2,5	41,0	48,0
27 x 2 x 2,5	42,0	49,0
30 x 2 x 2,5	43,5	51,0
37 x 2 x 2,5	47,0	55,0
2 x 3 x 0,5	13,0	15,5
3 x 3 x 0,5	13,5	16,0
4 x 3 x 0,5	15,0	17,5
5 x 3 x 0,5	16,0	19,0
6 x 3 x 0,5	17,5	20,5
7 x 3 x 0,5	17,5	20,5
8 x 3 x 0,5	18,5	22,0
10 x 3 x 0,5	21,5	25,5
12 x 3 x 0,5	22,5	26,0
2 x 3 x 0,75	13,5	16,5
3 x 3 x 0,75	14,5	17,0
4 x 3 x 0,75	16,0	18,5
5 x 3 x 0,75	17,5	20,0
6 x 3 x 0,75	18,5	21,5
7 x 3 x 0,75	18,5	21,5
8 x 3 x 0,75	20,0	23,5
10 x 2 x 0,75	23,5	27,0
12 x 3 x 0,75	24,0	28,0

Job Id: **262.1-008108-15**
Certificate No: **TAE000026F**

2 x 3 x 1,0	14,5	17,5
3 x 3 x 1,0	15,0	18,0
4 x 3 x 1,0	16,5	19,5
5 x 3 x 1,0	18,0	21,5
6 x 3 x 1,0	19,0	23,0
7 x 3 x 1,0	19,0	23,0
8 x 3 x 1,0	21,0	25,0
10 x 3 x 1,0	24,5	29,0
12 x 3 x 1,0	25,0	29,5
2 x 3 x 1,5	16,5	19,5
3 x 3 x 1,5	18,0	20,5
4 x 3 x 1,5	19,5	22,0
5 x 3 x 1,5	21,0	24,5
6 x 3 x 1,5	23,0	26,5
7 x 3 x 1,5	23,0	26,5
8 x 3 x 1,5	25,0	28,5
10 x 3 x 1,5	29,5	33,5
12 x 3 x 1,5	30,0	34,5
2 x 3 x 2,5	18,5	21,5
3 x 3 x 2,5	19,5	22,5
4 x 3 x 2,5	21,5	25,0
5 x 3 x 2,5	23,5	27,0
6 x 3 x 2,5	25,5	29,5
7 x 3 x 2,5	25,5	29,5
8 x 3 x 2,5	27,5	31,5
10 x 3 x 2,5	32,5	37,0
12 x 3 x 2,5	34,0	38,5
2 x 4 x 0,5	15,5	18,5
3 x 4 x 0,5	16,5	19,0
4 x 4 x 0,5	18,0	21,0
5 x 4 x 0,5	19,0	22,5
6 x 4 x 0,5	21,0	24,5
7 x 4 x 0,5	21,0	24,5

2 x 4 x 0,75	16,5	19,5
3 x 4 x 0,75	17,5	20,5
4 x 4 x 0,75	19,0	22,0
5 x 4 x 0,75	21,0	24,5
6 x 4 x 0,75	22,5	26,5
7 x 4 x 0,75	22,5	26,5
2 x 4 x 1,0	17,0	20,5
3 x 4 x 1,0	18,0	21,5
4 x 4 x 1,0	20,0	24,0
5 x 4 x 1,0	21,5	25,5
6 x 4 x 1,0	23,5	28,0
7 x 4 x 1,0	23,5	28,0
2 x 4 x 1,5	20,0	23,5
3 x 4 x 1,5	21,0	25,0
4 x 4 x 1,5	23,0	27,0
5 x 4 x 1,5	25,5	30,0
6 x 4 x 1,5	27,5	32,0
7 x 4 x 1,5	27,5	32,0
2 x 4 x 2,5	22,0	26,0
3 x 4 x 2,5	23,0	27,5
4 x 4 x 2,5	25,5	30,0
5 x 4 x 2,5	28,5	33,5
6 x 4 x 2,5	31,0	36,0
7 x 4 x 2,5	31,0	36,0

Application/Limitation

Control. Instrumentation and communication.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-376	2017-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	

Job Id: **262.1-008108-15**
Certificate No: **TAE000026F**

Marking of product

Hebei Huatong Wires & Cables Group Co.,Ltd –CHEH92 - size – 150/250 V – Lot no.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE