

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Electric Power Cable**

with type designation(s)

0.6/1 kV BU P110, FX-BU P110, BU, FX-BU

Issued to

TMC Co., Ltd**Cheonan-si Chungcheongnam-do, Korea**

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**IEC 60092-353 (2016-09)****IEC 60331-1/2 (2009-05)****IEC 60331-21 (1999-04)****IEC 60332-3-22 (2009-02)****IEC 60754-1/2 (2011-11)****IEC 61034-2 Ed. 3.1 (2013-06)****NEK TS 606 (2016)****Application :****General power and lighting. Flame retardant Cat.A. Fire resistant. Low smoke. Halogen free.
Mud resistant. Cold bend(-40°C)/Cold impact(-35°C)****Product(s) approved by this certificate is/are accepted for installation on all vessels classed
by DNV GL.****Rated voltage (kV) 0.6/1****Temp. class (°C) 90**Issued at **Busan** on **2017-07-01**This Certificate is valid until **2022-06-30**.for **DNV GL**DNV GL local station: **Seoul**Approval Engineer: **Eun Sook Kim**

.....

Michael Jost Auf der Stroth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-007573-5**
Certificate No: **TAE00002D8**

Product description

Type: 0.6/1 kV BU P110, FX-BU P110, BU, FX-BU

Conductors: Tinned stranded copper, Class 2 or Class 5(FX-types)
Fire resisting layer: Mica/glass tape
Core insulation: EPR
Outer sheath: SHF2 or SHF Mud

No. of Cores	Conductor Nominal Area (mm ²)
1	1.5
1	2.5
1	4
1	6
1	10
1	16
1	25
1	35
1	50
1	70
1	95
1	120
1	150
1	185
1	240
1	300
1	*400
1	*500
1	*630
2	1.5
2	2.5
2	4
2	6
2	10
2	16
2	25
2	35
2	50
2	70
2	95
2	120
2	150
2	185
2	240
2	300
2C+E	1.5
2C+E	2.5
2C+E	4
2C+E	6
2C+E	10
2C+E	16
2C	25
Earth	16

No. of Cores	Conductor Nominal Area (mm ²)
2C	35
Earth	25
2C	50
Earth	25
2C	70
Earth	35
2C	95
Earth	50
2C	120
Earth	70
2C	150
Earth	95
2C	185
Earth	95
2C	240
Earth	120
3	1.5
3	2.5
3	4
3	6
3	10
3	16
3	25
3	35
3	50
3	70
3	95
3	120
3	150
3	185
3	240
3	300
3C+E	1.5
3C+E	2.5
3C+E	4
3C+E	6
3C+E	10
3C+E	16
3C	25
Earth	16
3C	35
Earth	25

No. of Cores	Conductor Nominal Area (mm ²)
3C	50
Earth	25
3C	70
Earth	35
3C	95
Earth	50
3C	120
Earth	70
3C	150
Earth	95
3C	185
Earth	95
3C	240
Earth	120
4	1.5
4	2.5
4	4
4	6
4	10
4	16
4	25
4	35
4	50
4	70
4	95
4	120
4	150
4	185
4	240
4	300
4C+E	1.5
4C+E	2.5
4C+E	4
4C+E	6
4C+E	10
4C+E	16
4C	25
Earth	16
4C	35
Earth	25
4C	50
Earth	25
4C	70

No. of Cores	Conductor Nominal Area (mm ²)
Earth	35
4C	95
Earth	50
4C	120
Earth	70
4C	150
Earth	95
4C	185
Earth	95
4C	240
Earth	120
5	*1.5
5	*2.5
5	*4
5	*6
5	*10
5	*16
5	*25
5	*35
5	*50
5	*70
5	*95
5	*120
5	*150
5	*185
5	*240
*2	1.0
5	1.0
7	1.0

No. of Cores	Conductor Nominal Area (mm ²)
*8	1.0
9	1.0
*10	1.0
12	1.0
14	1.0
16	1.0
19	1.0
24	1.0
27	1.0
30	1.0
37	1.0
44	1.0
*2	1.5
5	1.5
7	1.5
*8	1.5
9	1.5
*10	1.5
12	1.5
14	1.5
16	1.5
19	1.5
24	1.5
27	1.5
30	1.5
37	1.5
44	1.5
*2	2.5
5	2.5

No. of Cores	Conductor Nominal Area (mm ²)
7	2.5
*8	2.5
9	2.5
*10	2.5
12	2.5
14	2.5
16	2.5
19	2.5
24	2.5
27	2.5
30	2.5
37	2.5
44	2.5
*2	4
5	4
7	4
*8	4
9	4
*10	4
12	4
14	4
16	4
19	4
24	4
27	4
30	4
37	4
44	4

* marked: Class 2 only (No Class 5)

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publication 60331.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg.45, 5.2 (provision to be taken to limit Fire Propagation along Bundles of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2008-02	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-353	2011-08	Single and multicore non-radial field power cables with extruded solid insulation for rated Voltages of 1 kV and 3 kV	
IEC 60092-360	2014	Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telocommunication cables	
IEC 60331-21	1999-04	Tests for electric cables under fire conditions - Circuit integrity - Part 21: Procedures and requirements - Cables of rated voltage up to and including 0,6/1,0 kV	90 min. test
IEC 60331-1/2	2009-05	Tests for electric cables under fire conditions – Part 1 : Test method for fire with shock at a temperature of at least 830°C for cables of rated voltage up to and including 0,6/1 kV and with an overall diameter exceeding 20mm Part 2 : Test method for fire with shock at a temperature of at least 830°C for cables of rated voltage up to and including 0,6/1 kV and with an overall diameter not exceeding 20mm	120 min. test
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Bunch test Category A
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen <0,5%
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity	Halogen free ≥4,3pH, ≤10μS/mm
IEC 61034-1/2	2013-06	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke >60%
CSA C22.2 No.0.3	2010	Test methods for electrical wires and cables	Cold bend (-40°C) Cold impact (-35°C)
UL 1581	2008-07	Sunlight resistant	
ASTM D 2863	2009	Oxygen index	Min. 32
NEK TS 606	2016	Cables for offshore installations – Halogen-free low smoke and flame-retardant / fire-resistant (HFFR-LS)	Oil & Mud resistant – Category a/b/c/d

Job Id: **262.1-007573-5**
Certificate No: **TAE00002D8**

Standard	Release	General description	Limitation
NEK TS 606	2016	Cables for offshore installations – Halogen-free low smoke and flame-retardant / fire-resistant (HFFR-LS)	Only for BU P110 and FX-BU P110 cables IEC 60331-1/2 test and Water spray test acc. to EN 50200:2015 Annex E or Water jet test acc. to BS 8491

Marking of product

0,6/1 kV BU P110, FX-BU P110, BU or FX-BU – Size – IEC 60331-1(120) or IEC 60331-2(120) – IEC 60332-3 Cat.A – TMC – Year of manufacture – Length

Periodical assessment

The scope of the retention/renewal survey is to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the survey are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routines (RT) checked (if not available tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE