

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Electric Power Cable

with type designation(s)
EXY, EXY-S, EXY-SEC

Issued to

Kukdong Electric Wire Co., Ltd.
Jincheon-gun, Chungcheongbuk-do, Korea

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft
IEC 60092-353 (2016-09)

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Rated voltage (kV) 0.6/1
Temp. class (°C) 90

Issued at **Busan** on **2018-05-17**

This Certificate is valid until **2019-03-26**.

DNV GL local station: **Seoul**

for **DNV GL**

Approval Engineer: **Eun Jin Lee**

Michael Jost Auf der Stroth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Type : EXY, EXY-S, EXY-SEC

Conductor: Stranded tinned annealed copper conductor, Class 2
(or enhanced class 2 for '-SEC' cable)
Insulation: HEPR + Mica tape
Individual screen: Tinned annealed copper wire braid ('-S' type only)
Outer sheath : PVC(ST2)

Type	No. of cores x conductor cross-section
EXY	1C, 2C, 3C, 4C x 1.5~300mm ² 2+E, 3+E, 4+E x 25~300mm ² 5C, 6C x 1.5~16mm ² 10C x 1.5 and 2.5mm ²
EXY-S	1C, 2C, 3C, 4C x 1.5~16mm ²
EXY-SEC	2C, 4C x 50~185mm ²

Application/Limitation

This cable is fire resistant according to IEC 60331.

The requirement of SOLAS Chapter II-1 Part D Reg. 45, 5.2 to limit Fire Propagation along Bunches of Cables or Wires are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-353	2016-09	Power cables for rated voltages 1kV and 3kV	
IEC 60092-360	2014-04	Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation, telecommunication cables	
IEC 60331-21	1999-04	Fire with shock-Electric cables under fire conditions-Circuit integrity	@750°C (90min)
IEC 60331-1/-2	2009-05	Fire with shock-Electric cables under fire conditions	@830°C(120min) with shock
IEC 60332-3-22	2009-02	Test for vertical flame spread of vertically mounted bunched wires or cables	Cat. A
IEC 60811-506	2012-03	Impact test at low temperature for insulations and sheaths	@-30 °C

Marking of product

0.6/1 kV - Cable type - Size - KUKDONG - IEC 60331(120) - IEC 60332-3 A - Year - Length

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation



Job Id: **262.1-027832-1**
Certificate No: **TAE00002UR**

- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE