

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Low Voltage Cable**

with type designation(s)
H-FLEX CTL PUR 250V, H-FLEX CTL C-PUR 250V

Issued to

Helkama Bica (Shanghai) Co. Ltd.
Shanghai, 020, China

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Highly flexible control cable for flexible use and fixed installations.

Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.

Type	Rated voltage (V)	Temp. class (°C)
H-FLEX CTL PUR 250V	150/250	90
H-FLEX CTL C-PUR 250V	150/250	90

Issued at **Høvik** on **2019-03-24**

This Certificate is valid until **2022-12-31**.

DNV GL local station: **Shanghai**

for **DNV GL**

Approval Engineer: **Ivar Bull**

.....
Trond Sjøvåg
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-009055-7**
Certificate No: **TAE0000352**

Product description

Type: H-FLEX CTL PUR 250V
H-FLEX CTL C-PUR 250V

Construction:

Conductor: Plain (optional tinned) stranded copper class 5

Core insulation: XLPE

Inner covering: Tape wrapping

Metal covering: Only H-FLEX CTL C-PUR:
Plain (optional tinned) copper wires braid. Filling factor >0,6

Outer sheath: PUR

No of cores:	Cross sectional area [mm ²]
2-37	0,5, 0,75

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

	Release	General description	Limitation
DNVGL-CP-0399	2016-03	Class Programme Electric cables	
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	Does not cover PUR outer sheath.
IEC 60092-376	2017-05	Electrical installations in ships - Part 376: Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60332-1-2	2015-07	Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW pre-mixed flame	
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
EN 50363-10-2	2006	Insulating, sheathing and covering materials for low voltage energy cables - Part 10-2: Miscellaneous sheathing compounds - Thermoplastic polyurethane	

Job Id: **262.1-009055-7**
Certificate No: **TAE0000352**

	Release	General description	Limitation
EN 50396-6.2	2005	Insulating, sheathing and covering materials for low voltage energy cables - Part 6: Halogen-free, crosss-linked sheathing compounds	

Marking of product

HELKAMA 3 - H-FLEX CTL PUR 250V – size – Lot No. or
HELKAMA 3 - H-FLEX CTL C-PUR 250V – size – Lot No.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE