

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Electric Power Cable**

with type designation(s)

RFOU P1 0,6/1kV, RFOU P1/P8 0,6/1 kV

Issued to

Untel Kablolari San. ve Tic. A.S.
Dilovasi, Turkey

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

Type	Rated voltage (kV)	Temp. class (°C)
RFOU P1 0,6/1kV	0,6/1	90
RFOU P1/P8 0,6/1 kV	0,6/1	90

Issued at **Hamburg** on **2019-01-18**This Certificate is valid until **2024-01-17**.for **DNV GL**DNV GL local station: **Istanbul**Approval Engineer: **Carsten Hunsalz**

Arne Schaarmann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Type: RFOU P1 0,6/1kV or RFOU P1/P8 0,6/1 kV

Construction:
Conductors: Tinned stranded copper class 2 or class 5
Core insulation: EPR or HEPR
Inner covering: Halogen free compound
Metal covering: Tinned copper wire braid
Outer sheath: SHF MUD

Number of cores x cross- section mm ²	Overall diameter mm
1 x 1,5	8,8
1 x 2,5	9,4
1 x 4	10,0
1 x 6	10,5
1 x 10	11,4
1 x 16	12,7
1 x 25	14,7
1 x 35	16,0
1 x 50	17,8
1 x 70	19,7
1 x 95	22,1
1 x 120	23,7
1 x 150	25,8
1 x 185	28,3
1 x 240	31,4
1 x 300	34,8
1 x 400	39,3
2 x 1,5	12,8
2 x 2,5	14,0
2 x 4	15,2
2 x 6	16,4
2 x 10	18,2
2 x 16	20,6
2 x 25	24,0
2 x 35	26,4
2 x 50	30,2
2 x 70	34,4
2 x 95	39,4
2 x 120	43,0
2 x 150	47,4
2 x 185	52,4
2 x 240	59,0

Number of cores x cross- section mm ²	Overall diameter mm
3 x 1,5	13,4
3 x 2,5	14,7
3 x 4	16,2
3 x 6	17,3
3 x 10	19,4
3 x 16	22,0
3 x 25	25,6
3 x 35	28,2
3 x 50	32,7
3 x 70	37,2
3 x 95	42,1
3 x 120	46,4
3 x 150	50,7
3 x 185	56,5
3 x 240	63,1
3 x 300	69,6
4 x 1,5	14,8
4 x 2,5	15,9
4 x 4	17,4
4 x 6	18,8
4 x 10	21,0
4 x 16	23,8
4 x 25	28,1
4 x 35	31,0
4 x 50	36,3
4 x 70	40,8
4 x 95	47,0
4 x 120	51,0
4 x 150	56,4
4 x 185	62,4
4 x 240	69,8

Number of cores x cross- section mm ²	Overall diameter mm
5 x 1,5	16,0
5 x 2,5	17,0
5 x 4	18,9
5 x 6	20,2
5 x 10	22,8
5 x 16	26,0
5 x 25	30,5
5 x 35	34,3
5 x 50	40,0
5 x 70	45,2
5 x 95	51,5
5 x 120	56,6
5 x 150	62,1
5 x 185	68,8
5 x 240	77,6
7 x 1,5	17,0
10 x 1,5	20,8
14 x 1,5	22,6
19 x 1,5	24,8
24 x 1,5	28,6
30 x 1,5	30,8
37 x 1,5	32,8
7 x 2,5	18,2
10 x 2,5	22,6
14 x 2,5	24,3
19 x 2,5	26,8
24 x 2,5	31,2
30 x 2,5	34,0
37 x 2,5	36,2

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

General power and lighting.
Flame retardant in bunch Cat. A. Halogen free. Low smoke.
Mud resistant.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-353	2016-09	Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
EC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2013-06	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance >60%
NEK TS 606	2009	Cables for offshore installations. Halogen-free and/or mud resistant. Technical specification.	

Marking of product

ÜNTEL – RFOU (NEK 606 P1 or P1/P8) – size – 0,6/1 kV - IEC 60332-3-22

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE