DNV·GL

Certificate No:
TAE00003D7

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Electric Power Cable

with type designation(s)
BOSTRIG-125 Type P, ...PCPEBS,
BOSTRIG-125 Type P, SPCPEBS2kV(HD),
BOSTRIG-125 Type P VFD

Issued to
Prysmian Cables and Systems USA, LLC
Highland Heights, KY, USA

is found to comply with
DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Power, Lighting and Control including VFD variants. CPE sheath.

Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.

Type	Rated voltage (kV)	Temp. class (°C)
BOSTRIG-125 Type P, ...PCPEBS	0,6/1	95
BOSTRIG-125 Type P, SPCPEBS2kV(HD)	2	95
BOSTRIG-125 Type P VFD	0,6/1	95

Issued at **Høvik** on **2020-11-17**
This Certificate is valid until **2024-12-31**.
DNV GL local station: **New York**

Approval Engineer: **Ivar Bull**

for **DNV GL**

Marta Alonso Pontes
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-007168-5**
Certificate No: **TAE00003D7**

Name and place of manufacturer:

Prysmian Power Cables and Systems, Taunton, MA 02780, United States.

Product description

Construction:

Conductor:	Tinned stranded copper
Insulation:	XLPO (Type P)
Filler:	Flame Retardant, non hygroscopic (as needed)
Inner sheath:	Thermoset CPE
Metal covering:	Bronze or Aluminum wire braid
Outer sheath:	Thermoset CPE

Number of cores x conductor cross-section		Type designation
mm²	AWG/ MCM	
1 x 7,57	8	SPCPEBS-8
1 x 12,5	6	SPCPEBS-6
1 x 18,6	5	SPCPEBS-5
1 x 21,5	4	SPCPEBS-4
1 x 25,6	3	SPCPEBS-3
1 x 30,7	2	SPCPEBS-2
1 x 46,0	1	SPCPEBS-1
1 x 56,3	1/0	SPCPEBS-1/0
1 x 66,5	2/0	SPCPEBS-2/0
1 x 92,1	3/0	SPCPEBS-3/0
1 x 7,57	8	SPCPEBS2KV-8
1 x 12,5	6	SPCPEBS2KV-6
1 x 18,6	5	SPCPEBS2KV-5
1 x 21,5	4	SPCPEBS2KV-4
1 x 25,6	3	SPCPEBS2KV-3
1 x 30,7	2	SPCPEBS2KV-2
1 x 46,0	1	SPCPEBS2KV-1
1 x 56,3	1/0	SPCPEBS2KV-1/0
1 x 66,5	2/0	SPCPEBS2KV-2/0
1 x 92,1	3/0	SPCPEBS2KV-3/0
1 x 112,6	4/0	SPCPEBS2KV(HD)-4/0
1 x 133,0	262	SPCPEBS2KV(HD)-262
1 x 158,6	313	SPCPEBS2KV(HD)-313
1 x 189,3	373	SPCPEBS2KV(HD)-373
1 x 225,1	444	SPCPEBS2KV(HD)-444
1 x 271,2	535	SPCPEBS2KV(HD)-535
1 x 327,5	646	SPCPEBS2KV(HD)-646
1 x 393,8	777	SPCPEBS2KV(HD)-777
1 x 562,8	1111	SPCPEBS2KV(HD)-1111
2 x 7,57	8	DPCPEBS-8
2 x 12,5	6	DPCPEBS-6
2 x 18,6	5	DPCPEBS-5
2 x 21,5	4	DPCPEBS-4
2 x 25,6	3	DPCPEBS-3
2 x 30,7	2	DPCPEBS-2
2 x 46,0	1	DPCPEBS-1
2 x 56,3	1/0	DPCPEBS-1/0
2 x 66,5	2/0	DPCPEBS-2/0
2 x 92,1	3/0	DPCPEBS-3/0

Number of cores x conductor cross-section		Type designation
mm²	AWG/ MCM	
2 x 112,6	4/0	DPCPEBS-4/0
2 x 133,0	262	DPCPEBS-262
2 x 158,6	313	DPCPEBS-313
2 x 189,3	373	DPCPEBS-373
2 x 225,1	444	DPCPEBS-444
2 x 271,2	535	DPCPEBS-535
2 x 327,5	646	DPCPEBS-646
2 x 393,8	777	DPCPEBS-777
3 x 7,57	8	TPCPEBS-8
3 x 12,5	6	TPCPEBS-6
3 x 18,6	5	TPCPEBS-5
3 x 21,5	4	TPCPEBS-4
3 x 25,6	3	TPCPEBS-3
3 x 30,7	2	TPCPEBS-2
3 x 46,0	1	TPCPEBS-1
3 x 56,3	1/0	TPCPEBS-1/0
3 x 66,5	2/0	TPCPEBS-2/0
3 x 92,1	3/0	TPCPEBS-3/0
3 x 112,6	4/0	TPCPEBS-4/0
3 x 133,0	262	TPCPEBS-262
3 x 158,6	313	TPCPEBS-313
3 x 189,3	373	TPCPEBS-373
3 x 225,1	444	TPCPEBS-444
3 x 271,2	535	TPCPEBS-535
3 x 327,5	646	TPCPEBS-646
3 x 393,8	777	TPCPEBS-777
4 x 7,57	8	FPCPEBS-8
4 x 12,5	6	FPCPEBS-6
4 x 18,6	5	FPCPEBS-5
4 x 21,5	4	FPCPEBS-4
4 x 25,6	3	FPCPEBS-3
4 x 30,7	2	FPCPEBS-2
4 x 46,0	1	FPCPEBS-1
4 x 56,3	1/0	FPCPEBS-1/0
4 x 66,5	2/0	FPCPEBS-2/0
4 x 92,1	3/0	FPCPEBS-3/0
4 x 112,6	4/0	FPCPEBS-4/0
4 x 133,0	262	FPCPEBS-262
4 x 158,6	313	FPCPEBS-313

Number of cores x conductor cross-section		Type designation
mm²	AWG/ MCM	
4 x 189,3	373	FPCPEBS-373
4 x 225,1	444	FPCPEBS-444
4 x 271,2	535	FPCPEBS-535
4 x 327,5	646	FPCPEBS-646
4 x 393,8	777	FPCPEBS-777
5 x 7,57	8	QPCPEBS-8
5 x 12,5	6	QPCPEBS-6
5 x 18,6	5	QPCPEBS-5
5 x 21,5	4	QPCPEBS-4
5 x 25,6	3	QPCPEBS-3
5 x 30,7	2	QPCPEBS-2
5 x 46,0	1	QPCPEBS-1
5 x 56,3	1/0	QPCPEBS-1/0
5 x 66,5	2/0	QPCPEBS-2/0
5 x 92,1	3/0	QPCPEBS-3/0
5 x 112,6	4/0	QPCPEBS-4/0
7 x 7,57	8	7PCPEBS-8
4 x 3,08	12	[FP-12/C(OS)14P-4]CPEBS-8
4 x 1,94	14	
4 x 7,57	8	[FP-8/C(OS)14P-4]CPEBS-8
4 x 1,94	14	
4 x 21,5	4	[FP-4/C(OS)14P-4]CPEBS-8
4 x 1,94	14	
4 x 30,7	2	[FP-2/C(OS)14P-4]CPEBS-8
4 x 1,94	14	
4 x 46,0	1	[FP-1/C(OS)14P-4]CPEBS-8
4 x 1,94	14	
2 x 18,6	5	[DP-2/FP-8/C14P-26/
4 x 7,57	8	TP(I/S)14P-3]CPEBS-38
26 x 1,94	14	
3x 2x 1,94	14	
7 x 6,0	9	[C9P-7/C13P-7/
7 x 2,5	13	C15P-12]CPEBS-26
12 x 1,5	15	
2 x 0,96	18	C18PCPEBS-2
3 x 0,96	18	C18PCPEBS-3
4 x 0,96	18	C18PCPEBS-4
5 x 0,96	18	C18PCPEBS-5
6 x 0,96	18	C18PCPEBS-6

Number of cores x conductor cross-section		Type designation
mm²	AWG/ MCM	
7 x 0,96	18	C18PCPEBS-7
8 x 0,96	18	C18PCPEBS-8
10 x 0,96	18	C18PCPEBS-10
12 x 0,96	18	C18PCPEBS-12
16 x 0,96	18	C18PCPEBS-16
20 x 0,96	18	C18PCPEBS-20
24 x 0,96	18	C18PCPEBS-24
30 x 0,96	18	C18PCPEBS-30
37 x 0,96	18	C18PCPEBS-37
44 x 0,96	18	C18PCPEBS-44
45 x 0,96	18	C18PCPEBS-45
60 x 0,96	18	C18PCPEBS-60
91 x 0,96	18	C18PCPEBS-91
2 x 1,23	16	C16PCPEBS-2
3 x 1,23	16	C16PCPEBS-3
4 x 1,23	16	C16PCPEBS-4
5 x 1,23	16	C16PCPEBS-5
6 x 1,23	16	C16PCPEBS-6
7 x 1,23	16	C16PCPEBS-7
8 x 1,23	16	C16PCPEBS-8
10 x 1,23	16	C16PCPEBS-10
12 x 1,23	16	C16PCPEBS-12
16 x 1,23	16	C16PCPEBS-16
18 x 1,23	16	C16PCPEBS-18
20 x 1,23	16	C16PCPEBS-20
22 x 1,23	16	C16PCPEBS-22
24 x 1,23	16	C16PCPEBS-24
30 x 1,23	16	C16PCPEBS-30
37 x 1,23	16	C16PCPEBS-37
44 x 1,23	16	C16PCPEBS-44
60 x 1,23	16	C16PCPEBS-60
91 x 1,23	16	C16PCPEBS-91
2 x 1,94	14	C14PCPEBS-2 or DPCPEBS-14
3 x 1,94	14	C14PCPEBS-3 or TPCPEBS-14
4 x 1,94	14	C14PCPEBS-4 or FPCPEBS-14
5 x 1,94	14	C14PCPEBS-5 or QPCPEBS-14
6 x 1,94	14	C14PCPEBS-6
7 x 1,94	14	C14PCPEBS-7
8 x 1,94	14	C14PCPEBS-8
10 x 1,94	14	C14PCPEBS-10
12 x 1,94	14	C14PCPEBS-12
14 x 1,94	14	C14PCPEBS-14
16 x 1,94	14	C14PCPEBS-16
19 x 1,94	14	C14PCPEBS-19
20 x 1,94	14	C14PCPEBS-20
24 x 1,94	14	C14PCPEBS-24
30 x 1,94	14	C14PCPEBS-30

Number of cores x conductor cross-section		Type designation
mm²	AWG/ MCM	
37 x 1,94	14	C14PCPEBS-37
44 x 1,94	14	C14PCPEBS-44
60 x 1,94	14	C14PCPEBS-60
91 x 1,94	14	C14PCPEBS-91
2 x 3,08	12	C12PCPEBS-2 or DPCPEBS-12
3 x 3,08	12	C12PCPEBS-3 or TPCPEBS-12
4 x 3,08	12	C12PCPEBS-4 or FPCPEBS-12
5 x 3,08	12	C12PCPEBS-5 or QPCPEBS-12
6 x 3,08	12	C12PCPEBS-6
7 x 3,08	12	C12PCPEBS-7
8 x 3,08	12	C12PCPEBS-8
10 x 3,08	12	C12PCPEBS-10
12 x 3,08	12	C12PCPEBS-12
16 x 3,08	12	C12PCPEBS-16
20 x 3,08	12	C12PCPEBS-20

Number of cores x conductor cross-section		Type designation
mm²	AWG/ MCM	
24 x 3,08	12	C12PCPEBS-24
30 x 3,08	12	C12PCPEBS-30
37 x 3,08	12	C12PCPEBS-37
44 x 3,08	12	C12PCPEBS-44
60 x 3,08	12	C12PCPEBS-60
91 x 3,08	12	C12PCPEBS-91
2 x 5,53	10	C10PCPEBS-2 or DPCPEBS-10
3 x 5,53	10	C10PCPEBS-3 or TPCPEBS-10
4 x 5,53	10	C10PCPEBS-4 or FPCPEBS-10
5 x 5,53	10	C10PCPEBS-5 or QPCPEBS-10
6 x 5,53	10	C10PCPEBS-6
7 x 5,53	10	C10PCPEBS-7
8 x 5,53	10	C10PCPEBS-8
9 x 5,53	10	C10PCPEBS-9
10 x 5,53	10	C10PCPEBS-10

VFD Cables:

Construction:
Conductor: Tinned stranded copper
Insulation: XLPO (Type P)
Ground conductors: Three symmetrically distributed reduced ground conductors in interstices
Filler: Flame Retardant, non hygroscopic (as needed)
Shield: Tinned copper braid with 95% coverage
Inner sheath: Thermoset CPE
Metal covering: Bronze or Aluminum wire braid
Outer sheath: Thermoset CPE

Number of cores x conductor cross-section:		Type designation
mm²	AWG/MCM	
3x 7.6 +3x 3.3	3x 8 AWG +3x 12 AWG	TP(OBS)CPEBS-8 w/grds
3x 12.5 +3x 3.3	3x 6 AWG +3x 12 AWG	TP(OBS)CPEBS-6 w/grds
3x 18.5 +3x 5.2	3x 5 AWG +3x 10 AWG	TP(OBS)CPEBS-5 w/grds
3x 21.1 +3x 5.2	3x 4 AWG +3x 10 AWG	TP(OBS)CPEBS-4 w/grds
3x 27.2 +3x 5.2	3x 3 AWG +3x 10 AWG	TP(OBS)CPEBS-3 w/grds
3x 34.0 +3x 5.2	3x 2 AWG +3x 10 AWG	TP(OBS)CPEBS-2 w/grds
3x 43.0 +3x 5.2	3x 1 AWG +3x10 AWG	TP(OBS)CPEBS-1 w/grds
3x 54.0 +3x 5.2	3x 1/0 AWG+3x 10 AWG	TP(OBS)CPEBS-1/0 w/grds
3x 70.0 +3x 7.6	3x 2/0 AWG +3x8 AWG	TP(OBS)CPEBS-2/0 w/grds
3x 86.0 +3x 7.6	3x 3/0 AWG +3x8 AWG	TP(OBS)CPEBS-3/0 w/grds
3x 109.0 +3x 12.5	3x 4/0 AWG +3x6 AWG	TP(OBS)CPEBS-4/0 w/grds
3x 132.0 +3x 12.5	3x 262 KCMIL +3x6 AWG	TP(OBS)CPEBS-262 w/grds
3x 159.0 +3x 12.5	3x 313 KCMIL +3x 6 AWG	TP(OBS)CPEBS-313 w/grds
3x 189.0 +3x 12.5	3x 373 KCMIL +3x 6 AWG	TP(OBS)CPEBS-373 w/grds
3x 227.0 +3x 18.6	3x 444 KCMIL +3x 5 AWG	TP(OBS)CPEBS-444 w/grds
3x 273.0 +3x18.6	3x 535 KCMIL +3x 5 AWG	TP(OBS)CPEBS-535 w/grds
3x 326.0 +3x18.6	3x 646 KCMIL +3x 5 AWG	TP(OBS)CPEBS-646 w/grds
3x 394.0 +3x18.6	3x 777 KCMIL +3x 5 AWG	TP(OBS)CPEBS-777 w/grds

3x 562.0 +3x 21.1	3x 1111 KCMIL +3x 4 AWG	TP(OBS)CPEBS-1111 w/grds

Application/Limitation
The requirements of SOLAS Amendments 1981 Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Tests carried out
Test according to IEEE 45 (2002), IEEE 1580 (2010) and IEC 60332-3 cat. A.

Marking of product
Draka 32 BOSTRIG P – Type designation - Number and size of conductors – Voltage or
Draka 32 BOSTRIG P – VFD - Type designation - Number and size of conductors - Voltage.

Periodical assessment
The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE