

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Low Voltage Cable**

with type designation(s)

250 V (FA-)MPYC & (FA-)MPYCE & (FA-)MPYC-S & (FA-)MPYCSLA & (FA-)TTPYC & (FA-)TTPYC-S & (FA-)TTPYCSLA & (FA-)TTPYC-SLA

Issued to

Seoul Electric Wire Co., Ltd.**Eumseong-gun, Chungcheongbuk-do, Republic of Korea**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft
IEC 60092-376 (2017-05)****Application :****Instrumentation and communication.****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Rated voltage (V) 250****Temp. class (°C) 90**Issued at **Busan** on **2019-04-09**This Certificate is valid until **2022-12-31**.for **DNV GL**DNV GL local station: **Seoul**Approval Engineer: **Eun Jin Lee**

.....

Andreas Kristoffersen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Type : 250 V (FA-)MPYC & (FA-)MPYCE & (FA-)MPYC-S & (FA-)MPYCSLA & (FA-)TTPYC & (FA-)TTPYC-S & (FA-)TTPYCSLA & (FA-)TTPYC-SLA

Conductors: Tinned stranded copper class 2 or class 5
Core insulation: EPR
Individual shield : Tinned copper wire braid ('S'type only)
Aluminium laminated tape with a drain wire ('SLA' type only)
Common shield : Aluminium laminated tape with a drain wire ('SLA' type only)
Inner sheath: PVC
Metal covering : Galvanized steel wire (C)

Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2
(FA-)MPYC	44 x 1,0 + E	37 x 1,5		19 x 2 x 1,5
2 x 1,0	77 x 1,0 + E	44 x 1,5	(FA-)TTPYC	24 x 2 x 1,5
4 x 1,0			1 x 2 x 0,75	30 x 2 x 1,5
7 x 1,0	2 x 1,5 + E	2 x 2,5	1 x 3 x 0,75	37 x 2 x 1,5
12 x 1,0	4 x 1,5 + E	4 x 2,5	1 x 4 x 0,75	48 x 2 x 1,5
19 x 1,0	7 x 1,5 + E	7 x 2,5	2 x 2 x 0,75	
27 x 1,0	12 x 1,5 + E	12 x 2,5	4 x 2 x 0,75	(FA-)TTPYC-S
37 x 1,0	19 x 1,5 + E	19 x 2,5	7 x 2 x 0,75	2 x 2 x 0,75
44 x 1,0	27 x 1,5 + E	27 x 2,5	10 x 2 x 0,75	4 x 2 x 0,75
77 x 1,0	37 x 1,5 + E	37 x 2,5	14 x 2 x 0,75	7 x 2 x 0,75
	44 x 1,5 + E	44 x 2,5	19 x 2 x 0,75	10 x 2 x 0,75
2 x 1,5	77 x 1,5 + E		24 x 2 x 0,75	14 x 2 x 0,75
4 x 1,5		(FA-)MPYCSLA	30 x 2 x 0,75	19 x 2 x 0,75
7 x 1,5	2 x 2,5 + E	2 x 1,0	37 x 2 x 0,75	24 x 2 x 0,75
12 x 1,5	4 x 2,5 + E	4 x 1,0	48 x 2 x 0,75	30 x 2 x 0,75
19 x 1,5	7 x 2,5 + E	7 x 1,0		37 x 2 x 0,75
27 x 1,5	12 x 2,5 + E	12 x 1,0	1 x 2 x 1,0	48 x 2 x 0,75
37 x 1,5	19 x 2,5 + E	19 x 1,0	1 x 3 x 1,0	
44 x 1,5	27 x 2,5 + E	27 x 1,0	1 x 4 x 1,0	2 x 2 x 1,0
77 x 1,5	37 x 2,5 + E	37 x 1,0	2 x 2 x 1,0	4 x 2 x 1,0
	44 x 2,5 + E	44 x 1,0	4 x 2 x 1,0	7 x 2 x 1,0
2 x 2,5	77 x 2,5 + E		7 x 2 x 1,0	10 x 2 x 1,0
4 x 2,5		2 x 1,5	10 x 2 x 1,0	14 x 2 x 1,0
7 x 2,5	(FA-)MPYC-S	4 x 1,5	14 x 2 x 1,0	19 x 2 x 1,0
12 x 2,5	2 x 1,0	7 x 1,5	19 x 2 x 1,0	24 x 2 x 1,0
19 x 2,5	4 x 1,0	12 x 1,5	24 x 2 x 1,0	30 x 2 x 1,0
27 x 2,5	7 x 1,0	19 x 1,5	30 x 2 x 1,0	37 x 2 x 1,0
37 x 2,5	12 x 1,0	27 x 1,5	37 x 2 x 1,0	48 x 2 x 1,0
44 x 2,5	19 x 1,0	37 x 1,5	48 x 2 x 1,0	
77 x 2,5	27 x 1,0	44 x 1,5		2 x 2 x 1,5
	37 x 1,0		1 x 2 x 1,5	4 x 2 x 1,5
(FA-)MPYCE	44 x 1,0	2 x 2,5	1 x 3 x 1,5	7 x 2 x 1,5
2 x 1,0 + E		4 x 2,5	1 x 4 x 1,5	10 x 2 x 1,5
4 x 1,0 + E	2 x 1,5	7 x 2,5	2 x 2 x 1,5	14 x 2 x 1,5
7 x 1,0 + E	4 x 1,5	12 x 2,5	4 x 2 x 1,5	19 x 2 x 1,5
12 x 1,0 + E	7 x 1,5	19 x 2,5	7 x 2 x 1,5	24 x 2 x 1,5
19 x 1,0 + E	12 x 1,5	27 x 2,5	10 x 2 x 1,5	30 x 2 x 1,5
27 x 1,0 + E	19 x 1,5	37 x 2,5	14 x 2 x 1,5	37 x 2 x 1,5
37 x 1,0 + E	27 x 1,5	44 x 2,5		48 x 2 x 1,5

Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2	Number of cores x conductor cross-section mm2
	1 x 4 x 1.0	7 x 2 x 1.5	14 x 2 x 0,75	30 x 2 x 1.0
(FA-)TTPYCSLA	2 x 2 x 1.0	10 x 2 x 1.5	19 x 2 x 0,75	37 x 2 x 1.0
1 x 2 x 0,75	4 x 2 x 1.0	14 x 2 x 1.5	24 x 2 x 0,75	48 x 2 x 1.0
1 x 3 x 0,75	7 x 2 x 1.0	19 x 2 x 1.5	30 x 2 x 0,75	
1 x 4 x 0,75	10 x 2 x 1.0	24 x 2 x 1.5	37 x 2 x 0,75	1 x 2 x 1.5
2 x 2 x 0,75	14 x 2 x 1.0	30 x 2 x 1.5	48 x 2 x 0,75	1 x 3 x 1.5
4 x 2 x 0,75	19 x 2 x 1.0	37 x 2 x 1.5		1 x 4 x 1.5
7 x 2 x 0,75	24 x 2 x 1.0	48 x 2 x 1.5	1 x 2 x 1.0	2 x 2 x 1.5
10 x 2 x 0,75	30 x 2 x 1.0		1 x 3 x 1.0	4 x 2 x 1.5
14 x 2 x 0,75	37 x 2 x 1.0	(FA-)TTPYC- SLA	1 x 4 x 1.0	7 x 2 x 1.5
19 x 2 x 0,75	48 x 2 x 1.0		2 x 2 x 1.0	10 x 2 x 1.5
24 x 2 x 0,75		1 x 2 x 0,75	4 x 2 x 1.0	14 x 2 x 1.5
30 x 2 x 0,75	1 x 2 x 1.5	1 x 3 x 0,75	7 x 2 x 1.0	19 x 2 x 1.5
37 x 2 x 0,75	1 x 3 x 1.5	1 x 4 x 0,75	10 x 2 x 1.0	24 x 2 x 1.5
48 x 2 x 0,75	1 x 4 x 1.5	2 x 2 x 0,75	14 x 2 x 1.0	30 x 2 x 1.5
	2 x 2 x 1.5	4 x 2 x 0,75	19 x 2 x 1.0	37 x 2 x 1.5
1 x 2 x 1.0	4 x 2 x 1.5	7 x 2 x 0,75	24 x 2 x 1.0	48 x 2 x 1.5
1 x 3 x 1.0		10 x 2 x 0,75		

Application/Limitation

The requirement of SOLAS Chapter II-1 Part D Reg.45, 5.2 to limit Fire Propagation along Bunches of Cables or Wires are fulfilled without any additional measures for 'FA-' type only.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-376	2017-05	Cables for control and instrumentation circuits 150/250V(300V)	
IEC 60332-1	2015-07	Test for vertical flame propagation for a single insulated wire or cable	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Bunch test Category A

Marking of product

250V – Type designation – Size – IEC 60332-1 – SEOUL – Year of manufacture – Length

For 'FA-'type,

250V – Type designation – Size – IEC 60332-1 – IEC 60332-3A – SEOUL – Year of manufacture – Length

Periodical assessment

Job Id: **262.1-003852-5**
Certificate No: **TAE00003FW**

The scope of the retention/renewal survey is to verify that the conditions stipulated for the Type Approval Certificate are complied with and that no alterations are made to the design and/or the material of product.

The main elements of the survey are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Check of the results from Production Sample Tests(PST) and Routine Tests(RT) (if not available, PSTand RT are to be carried out)
- Review of type approval documentation
- Review of possible changes in design, material and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE