DNV·GL

Certificate No:
TAE00003G2

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Electric Power Cable

with type designation(s)
0.6/1 kV FR-(FA-)SPYC & FR-(FA-)SPYCB & FR-(FA-)DPYC & FR-(FA-)TPYC & FR-(FA-)FPYC & FR-(FA-)DPYCE & FR-(FA-)TPYCE & FR-(FA-)FPYCE & FR-(FA-)DPYCSLA & FR-(FA-)TPYCSLA & FR-(FA-)MPYC

Issued to
Seoul Electric Wire Co., Ltd.
Eumseong-gun, Chungcheongbuk-do, Republic of Korea

is found to comply with
DNV GL rules for classification – Ships, offshore units, and high speed and light craft
IEC 60092-353 (2016-09)

Application :

General power and lighting.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.
Rated voltage (kV) 0.6/1
Temp. class (°C) 90

Issued at **Busan** on **2019-04-09**
This Certificate is valid until **2022-12-31**.
DNV GL local station: **Seoul**

Approval Engineer: **Eun Jin Lee**

for **DNV GL**

Andreas Kristoffersen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-003852-5**
Certificate No: **TAE00003G2**

Product description

Type : 0.6/1 kV FR-(FA-)SPYC & FR-(FA-)SPYCB & FR-(FA-)DPYC & FR-(FA-)TPYC & FR-(FA-)FPYC & FR-(FA-)DPYCE & FR-(FA-)TPYCE & FR-(FA-)FPYCE & FR-(FA-)DPYCSLA & FR-(FA-)TPYCSLA & FR-(FA-)MPYC

Conductors: Tinned stranded copper class 2 or class 5
Core insulation: EPR + Mica
Common shield : Aluminium laminated tape with a drain wire ('SLA' type only)
Inner sheath: PVC
Metal covering : Galvanized steel wire (C) / Copper alloy wire braid (CB)

Number of cores x conductor cross-section mm²
FR-(FA-)SPYC & FR-(FA-)SPYCB
1 x 1,5
1 x 2,5
1 x 4
1 x 6
1 x 10
1 x 16
1 x 25
1 x 35
1 x 50
1 x 70
1 x 95
1 x 120
1 x 150
1 x 185
1 x 240
1 x 300
FR-(FA-)DPYC
2 x 1,5
2 x 2,5
2 x 4
2 x 6
2 x 10
2 x 16
2 x 25
2 x 35

Number of cores x conductor cross-section mm²
2 x 50
2 x 70
2 x 95
2 x 120
2 x 150
2 x 185
FR-(FA-)TPYC
3 x 1,5
3 x 2,5
3 x 4
3 x 6
3 x 10
3 x 16
3 x 25
3 x 35
3 x 50
3 x 70
3 x 95
3 x 120
3 x 150
3 x 185
FR-(FA-)FPYC
4 x 1,5
4 x 2,5
4 x 4

Number of cores x conductor cross-section mm²
4 x 6
4 x 10
4 x 16
4 x 25
4 x 35
4 x 50
4 x 70
4 x 95
4 x 120
4 x 150
4 x 185
FR-(FA-)DPYCE
2 x 1,5 + E
2 x 2,5 + E
2 x 4 + E
2 x 6 + E
2 x 10 + E
2 x 16 + E
2 x 25 + E
2 x 35 + E
2 x 50 + E
2 x 70 + E
2 x 95 + E
2 x 120 + E
2 x 150 + E
2 x 185 + E

Number of cores x conductor cross-section mm²
FR-(FA-)TPYCE
3 x 1,5 + E
3 x 2,5 + E
3 x 4 + E
3 x 6 + E
3 x 10 + E
3 x 16 + E
3 x 25 + E
3 x 35 + E
3 x 50 + E
3 x 70 + E
3 x 95 + E
3 x 120 + E
3 x 150 + E
3 x 185 + E
FR-(FA-)FPYCE
4 x1,5 + E
4 x 2,5 + E
4 x 4 + E
4 x 6 + E
4 x 10 + E
4 x 16 + E
4 x 25 + E
4 x 35 + E
4 x 50 + E

Number of cores x conductor cross-section mm²
4 x 70 + E
4 x 95 + E
4 x 120 + E
4 x 150 + E
4 x 185 + E
FR-(FA-)DPYCSLA & FR-(FA-)TPYCSLA
2 x 1,5
2 x 2,5
2 x 4
3 x 1,5
3 x 2,5
3 x 4
FR-(FA-)MPYC
2 x 1,0
4 x 1,0
7 x 1,0
12 x 1,0
19 x 1,0
27 x 1,0
37 x 1,0
44 x 1,0
77 x 1,0

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publication 60331.

The requirement of SOLAS Chapter II-1 Part D Reg.45, 5.2 to limit Fire Propagation along Bunches of Cables or Wires are fulfilled without any additional measures for 'FA- ' type only.

The single core cable with galvanized steel wire braid shall not be used to A.C. circuits exceeding 20A or D.C. circuits with high ripple content.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-353	2016-09	Power cables for rated voltages 1kV and 3kV	
IEC 60331-1/-2	2009-05	Fire resistance / Circuit integrity – Test method for fire *with shock* at temperature of at least 830ºC for cables rated up to and including 0,6/1 kV	@ 830 °C w/shock (120)
IEC 60332-1	2015-07	Test for vertical flame propagation for a single insulated wire or cable	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Bunch test Category A

Marking of product

0.6/1 kV – Type designation – Size – IEC 60331(120) – IEC 60332-1 – SEOUL – Year of manufacture – Length

For 'FA-' type,
0.6/1 kV – Type designation – Size – IEC 60331(120) – IEC 60332-1 – IEC 60332-3 A – SEOUL – Year of manufacture – Length

Periodical assessment

The scope of the retention/renewal survey is to verify that the conditions stipulated for the Type Approval Certificate are complied with and that no alterations are made to the design and/or the material of product.

The main elements of the survey are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Check of the results from Production Sample Tests(PST) and Routine Tests(RT) (if not available, PSTand RT are to be carried out)
- Review of type approval documentation
- Review of possible changes in design, material and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE