

TYPE APPROVAL CERTIFICATE

This is to certify:**That the High Voltage Cable**

with type designation(s)

**BOSTRIG MHV-5(LS)BS 1,8/3 kV,
BOSTRIG MHV-8(LS)BS 3,6/6 kV,
BOSTRIG MHV-8(LS)BS 6/10 kV,
BOSTRIG MHV-15(LS)BS 8,7/15 kV,
BOSTRIG MHV-15(LS)BS12/20 kV**

Issued to

**Prysmian Cables and Systems USA, LLC
Highland Heights, KY , USA**

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Power.**

Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.

Type	Rated voltage (kV)	Temp. class (°C)
BOSTRIG MHV-5(LS)BS 1,8/3 kV	1,8/3	90
BOSTRIG MHV-8(LS)BS 3,6/6 kV	3,6/6	90
BOSTRIG MHV-8(LS)BS 6/10 kV	6/10	90
BOSTRIG MHV-15(LS)BS 8,7/15 kV	8,7/15	90
BOSTRIG MHV-15(LS)BS12/20 kV	12/20	90

Issued at **Høvik** on **2020-09-21**This Certificate is valid until **2025-08-29**.for **DNV GL**DNV GL local station: **New York**Approval Engineer: **Ivar Bull**

Marta Alonso Pontes
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Place of Manufacturer

Prysmian Power Cables and Systems, Taunton, MA 02780, United States

Product description

BOSTRIG MHV-5(LS)BS 1,8/3 kV
BOSTRIG MHV-8(LS)BS 3,6/6 kV
BOSTRIG MHV-8(LS)BS 6/10 kV
BOSTRIG MHV-15(LS)BS 8,7/15 kV
BOSTRIG MHV-15(LS)BS 12/20 kV

Construction:

Conductors: Tinned, rope stranded copper
Core insulation: EPR
Screening: Tinned copper wire braid
Inner sheath: SHF2
Metal covering: Bronze wire braid
Outer sheath: SHF2

BOSTRIG MHV-5(LS)BS 1,8/3 kV					
		DRAKA Cable Type Designation	IEEE Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM			mm	Inches
1 x 7,57	8	MHV-5(LS)BS-8	SELBS5KV-8	22,35	0,880
1 x 12,5	6	MHV-5(LS)BS-6	SELBS5KV-6	23,88	0,940
1 x 18,6	5	MHV-5(LS)BS-5	SELBS5KV-5	24,64	0,970
1 x 21,5	4	MHV-5(LS)BS-4	SELBS5KV-4	25,65	1,010
1 x 30,7	2	MHV-5(LS)BS-2	SELBS5KV-2	27,43	1,080
1 x 46,0	1	MHV-5(LS)BS-1	SELBS5KV-1	29,72	1,170
1 x 56,3	1/0	MHV-5(LS)BS-1/0	SELBS5KV-1/0	30,99	1,220
1 x 66,5	2/0	MHV-5(LS)BS-2/0	SELBS5KV-2/0	31,50	1,240
1 x 92,1	3/0	MHV-5(LS)BS-3/0	SELBS5KV-3/0	34,29	1,350
1 x 112,6	4/0	MHV-5(LS)BS-4/0	SELBS5KV-4/0	35,31	1,390
1 x 133,0	262	MHV-5(LS)BS-262	SELBS5KV-262	36,58	1,440
1 x 158,6	313	MHV-5(LS)BS-313	SELBS5KV-313	38,86	1,530
1 x 189,3	373	MHV-5(LS)BS-373	SELBS5KV-373	40,64	1,600
1 x 225,1	444	MHV-5(LS)BS-444	SELBS5KV-444	44,20	1,740
1 x 271,2	535	MHV-5(LS)BS-535	SELBS5KV-535	46,74	1,840
1 x 327,5	646	MHV-5(LS)BS-646	SELBS5KV-646	49,78	1,960
1 x 393,8	777	MHV-5(LS)BS-777	SELBS5KV-777	53,09	2,090
1 x 562,8	1111	MHV-5(LS)BS-1111	SELBS5KV-1111	59,44	2,340
3 x 7,57	8	MHV3-5(LS)BS-8	TELBS5KV-8	38,61	1,520
3 x 12,5	6	MHV3-5(LS)BS-6	TELBS5KV-6	41,91	1,650
3 x 18,6	5	MHV3-5(LS)BS-5	TELBS5KV-5	45,72	1,800
3 x 21,5	4	MHV3-5(LS)BS-4	TELBS5KV-4	47,50	1,870
3 x 30,7	2	MHV3-5(LS)BS-2	TELBS5KV-2	51,56	2,030
3 x 46,0	1	MHV3-5(LS)BS-1	TELBS5KV-1	54,86	2,160
3 x 56,3	1/0	MHV3-5(LS)BS-1/0	TELBS5KV-1/0	57,91	2,280
3 x 66,5	2/0	MHV3-5(LS)BS-2/0	TELBS5KV-2/0	58,93	2,320
3 x 92,1	3/0	MHV3-5(LS)BS-3/0	TELBS5KV-3/0	65,02	2,560
3 x 112,6	4/0	MHV3-5(LS)BS-4/0	TELBS5KV-4/0	68,07	2,680
3 x 133,0	262	MHV3-5(LS)BS-262	TELBS5KV-262	72,64	2,860
3 x 158,6	313	MHV3-5(LS)BS-313	TELBS5KV-313	77,72	3,060
3 x 189,3	373	MHV3-5(LS)BS-373	TELBS5KV-373	81,79	3,220
3 x 225,1	444	MHV3-5(LS)BS-444	TELBS5KV-444	85,85	3,380
3 x 271,2	535	MHV3-5(LS)BS-535	TELBS5KV-535	91,19	3,590

BOSTRIG MHV-5(LS)BS 1,8/3 kV					
		DRAKA Cable Type Designation	IEEE Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM			mm	Inches
3 x 327,5	646	MHV3-5(LS)BS-646	TELBS5KV-646	98,04	3,860
3 x 393,8	777	MHV3-5(LS)BS-777	TELBS5KV-777	103,38	4,070
3 x 562,8	1111	MHV3-5(LS)BS-1111	TELBS5KV-1111	118,36	4,660
4 x 7,57	8	MHV4-5(LS)BS-8	FELBS5KV-8	42,42	1,670
4 x 12,5	6	MHV4-5(LS)BS-6	FELBS5KV-6	47,75	1,880
4 x 18,6	5	MHV4-5(LS)BS-5	FELBS5KV-5	50,29	1,980
4 x 21,5	4	MHV4-5(LS)BS-4	FELBS5KV-4	52,83	2,080
4 x 30,7	2	MHV4-5(LS)BS-2	FELBS5KV-2	56,39	2,220
4 x 46,0	1	MHV4-5(LS)BS-1	FELBS5KV-1	60,20	2,370
4 x 56,3	1/0	MHV4-5(LS)BS-1/0	FELBS5KV-1/0	63,75	2,510
4 x 66,5	2/0	MHV4-5(LS)BS-2/0	FELBS5KV-2/0	64,77	2,550
4 x 92,1	3/0	MHV4-5(LS)BS-3/0	FELBS5KV-3/0	73,91	2,910
4 x 112,6	4/0	MHV4-5(LS)BS-4/0	FELBS5KV-4/0	77,22	3,040
4 x 133,0	262	MHV4-5(LS)BS-262	FELBS5KV-262	80,77	3,180
4 x 158,6	313	MHV4-5(LS)BS-313	FELBS5KV-313	86,36	3,400
4 x 189,3	373	MHV4-5(LS)BS-373	FELBS5KV-373	91,19	3,590
4 x 225,1	444	MHV4-5(LS)BS-444	FELBS5KV-444	95,50	3,760
4 x 271,2	535	MHV4-5(LS)BS-535	FELBS5KV-535	101,60	4,000
4 x 327,5	646	MHV4-5(LS)BS-646	FELBS5KV-646	109,22	4,300
4 x 393,8	777	MHV4-5(LS)BS-777	FELBS5KV-777	115,32	4,540
4 x 562,8	1111	MHV4-5(LS)BS-1111	FELBS5KV-1111	132,33	5,210

BOSTRIG MHV-8(LS)BS 3,6/6 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
1 x 12,5	6	MHV-8(LS)BS-6	25,15	0,990
1 x 18,6	5	MHV-8(LS)BS-5	26,16	1,030
1 x 21,5	4	MHV-8(LS)BS-4	26,92	1,060
1 x 30,7	2	MHV-8(LS)BS-2	29,46	1,160
1 x 46,0	1	MHV-8(LS)BS-1	30,99	1,220
1 x 56,3	1/0	MHV-8(LS)BS-1/0	32,26	1,270
1 x 66,5	2/0	MHV-8(LS)BS-2/0	32,77	1,290
1 x 92,1	3/0	MHV-8(LS)BS-3/0	35,31	1,390
1 x 112,6	4/0	MHV-8(LS)BS-4/0	36,58	1,440
1 x 133,0	262	MHV-8(LS)BS-262	37,85	1,490
1 x 158,6	313	MHV-8(LS)BS-313	40,13	1,580
1 x 189,3	373	MHV-8(LS)BS-373	41,91	1,650
1 x 225,1	444	MHV-8(LS)BS-444	45,21	1,780
1 x 271,2	535	MHV-8(LS)BS-535	47,75	1,880
1 x 327,5	646	MHV-8(LS)BS-646	51,56	2,030
1 x 393,8	777	MHV-8(LS)BS-777	54,10	2,130
1 x 562,8	1111	MHV-8(LS)BS-1111	60,20	2,370
3 x 12,5	6	MHV3-8(LS)BS-6	46,74	1,840
3 x 18,6	5	MHV3-8(LS)BS-5	48,77	1,920
3 x 21,5	4	MHV3-8(LS)BS-4	50,55	1,990
3 x 30,7	2	MHV3-8(LS)BS-2	54,36	2,140
3 x 46,0	1	MHV3-8(LS)BS-1	57,91	2,280
3 x 56,3	1/0	MHV3-8(LS)BS-1/0	60,96	2,400
3 x 66,5	2/0	MHV3-8(LS)BS-2/0	61,72	2,430

BOSTRIG MHV-8(LS)BS 3,6/6 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
3 x 92,1	3/0	MHV3-8(LS)BS-3/0	67,82	2,670
3 x 112,6	4/0	MHV3-8(LS)BS-4/0	72,39	2,850
3 x 133,0	262	MHV3-8(LS)BS-262	75,44	2,970
3 x 158,6	313	MHV3-8(LS)BS-313	80,52	3,170
3 x 189,3	373	MHV3-8(LS)BS-373	84,33	3,320
3 x 225,1	444	MHV3-8(LS)BS-444	88,39	3,480
3 x 271,2	535	MHV3-8(LS)BS-535	93,98	3,700
3 x 327,5	646	MHV3-8(LS)BS-646	100,08	3,940
3 x 393,8	777	MHV3-8(LS)BS-777	105,16	4,140
3 x 562,8	1111	MHV3-8(LS)BS-1111	120,40	4,740
4 x 12,5	6	MHV4-8(LS)BS-6	52,32	2,060
4 x 18,6	5	MHV4-8(LS)BS-5	54,61	2,150
4 x 21,5	4	MHV4-8(LS)BS-4	56,39	2,220
4 x 30,7	2	MHV4-8(LS)BS-2	59,94	2,360
4 x 46,0	1	MHV4-8(LS)BS-1	64,26	2,530
4 x 56,3	1/0	MHV4-8(LS)BS-1/0	67,56	2,660
4 x 66,5	2/0	MHV4-8(LS)BS-2/0	68,58	2,700
4 x 92,1	3/0	MHV4-8(LS)BS-3/0	77,22	3,040
4 x 112,6	4/0	MHV4-8(LS)BS-4/0	80,77	3,180
4 x 133,0	262	MHV4-8(LS)BS-262	83,82	3,300
4 x 158,6	313	MHV4-8(LS)BS-313	89,41	3,520
4 x 189,3	373	MHV4-8(LS)BS-373	94,23	3,710
4 x 225,1	444	MHV4-8(LS)BS-444	98,81	3,890
4 x 271,2	535	MHV4-8(LS)BS-535	104,90	4,130
4 x 327,5	646	MHV4-8(LS)BS-646	111,76	4,400
4 x 393,8	777	MHV4-8(LS)BS-777	117,60	4,630
4 x 562,8	1111	MHV4-8(LS)BS-1111	134,62	5,300

BOSTRIG MHV-8(LS)BS 6/10 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
1 x 18,6	5	MHV-8a(LS)BS-5	28,45	1,120
1 x 21,5	4	MHV-8a(LS)BS-4	29,21	1,150
1 x 30,7	2	MHV-8a(LS)BS-2	30,73	1,210
1 x 46,0	1	MHV-8a(LS)BS-1	32,26	1,270
1 x 56,3	1/0	MHV-8a(LS)BS-1/0	33,53	1,320
1 x 66,5	2/0	MHV-8a(LS)BS-2/0	34,04	1,340
1 x 92,1	3/0	MHV-8a(LS)BS-3/0	36,58	1,440
1 x 112,6	4/0	MHV-8a(LS)BS-4/0	38,10	1,500
1 x 133,0	262	MHV-8a(LS)BS-262	39,88	1,570
1 x 158,6	313	MHV-8a(LS)BS-313	41,66	1,640
1 x 189,3	373	MHV-8a(LS)BS-373	44,96	1,770
1 x 225,1	444	MHV-8a(LS)BS-444	46,99	1,850
1 x 271,2	535	MHV-8a(LS)BS-535	49,28	1,940
1 x 327,5	646	MHV-8a(LS)BS-646	52,83	2,080
1 x 393,8	777	MHV-8a(LS)BS-777	55,63	2,190
1 x 562,8	1111	MHV-8a(LS)BS-1111	61,21	2,410
3 x 18,6	5	MHV3-8a(LS)BS-5	52,32	2,060
3 x 21,5	4	MHV3-8a(LS)BS-4	53,85	2,120

BOSTRIG MHV-8(LS)BS 6/10 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
3 x 30,7	2	MHV3-8a(LS)BS-2	56,90	2,240
3 x 46,0	1	MHV3-8a(LS)BS-1	60,45	2,380
3 x 56,3	1/0	MHV3-8a(LS)BS-1/0	63,50	2,500
3 x 66,5	2/0	MHV3-8a(LS)BS-2/0	64,52	2,540
3 x 92,1	3/0	MHV3-8a(LS)BS-3/0	72,14	2,840
3 x 112,6	4/0	MHV3-8a(LS)BS-4/0	74,93	2,950
3 x 133,0	262	MHV3-8a(LS)BS-262	78,99	3,110
3 x 158,6	313	MHV3-8a(LS)BS-313	83,06	3,270
3 x 189,3	373	MHV3-8a(LS)BS-373	87,38	3,440
3 x 225,1	444	MHV3-8a(LS)BS-444	91,44	3,600
3 x 271,2	535	MHV3-8a(LS)BS-535	96,77	3,810
3 x 327,5	646	MHV3-8a(LS)BS-646	102,36	4,030
3 x 393,8	777	MHV3-8a(LS)BS-777	108,71	4,280
3 x 562,8	1111	MHV3-8a(LS)BS-1111	121,92	4,800
4 x 18,6	5	MHV4-8a(LS)BS-5	57,66	2,270
4 x 21,5	4	MHV4-8a(LS)BS-4	59,18	2,330
4 x 30,7	2	MHV4-8a(LS)BS-2	62,74	2,470
4 x 46,0	1	MHV4-8a(LS)BS-1	66,80	2,630
4 x 56,3	1/0	MHV4-8a(LS)BS-1/0	71,88	2,830
4 x 66,5	2/0	MHV4-8a(LS)BS-2/0	73,15	2,880
4 x 92,1	3/0	MHV4-8a(LS)BS-3/0	80,26	3,160
4 x 112,6	4/0	MHV4-8a(LS)BS-4/0	83,57	3,290
4 x 133,0	262	MHV4-8a(LS)BS-262	88,14	3,470
4 x 158,6	313	MHV4-8a(LS)BS-313	92,46	3,640
4 x 189,3	373	MHV4-8a(LS)BS-373	97,28	3,830
4 x 225,1	444	MHV4-8a(LS)BS-444	101,85	4,010
4 x 271,2	535	MHV4-8a(LS)BS-535	107,95	4,250
4 x 327,5	646	MHV4-8a(LS)BS-646	114,55	4,510
4 x 393,8	777	MHV4-8a(LS)BS-777	121,92	4,800
4 x 562,8	1111	MHV4-8a(LS)BS-1111	136,40	5,370

BOSTRIG MHV-15(LS)BS 8,7/15 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
1 x 30,7	2	MHV-15(LS)BS-2	32,26	1,270
1 x 46,0	1	MHV-15(LS)BS-1	33,78	1,330
1 x 56,3	1/0	MHV-15(LS)BS-1/0	35,31	1,390
1 x 66,5	2/0	MHV-15(LS)BS-2/0	35,81	1,410
1 x 92,1	3/0	MHV-15(LS)BS-3/0	38,86	1,530
1 x 112,6	4/0	MHV-15(LS)BS-4/0	40,13	1,580
1 x 133,0	262	MHV-15(LS)BS-262	41,66	1,640
1 x 158,6	313	MHV-15(LS)BS-313	44,70	1,760
1 x 189,3	373	MHV-15(LS)BS-373	46,99	1,850
1 x 225,1	444	MHV-15(LS)BS-444	48,77	1,920
1 x 271,2	535	MHV-15(LS)BS-535	52,07	2,050
1 x 327,5	646	MHV-15(LS)BS-646	54,61	2,150
1 x 393,8	777	MHV-15(LS)BS-777	57,40	2,260
1 x 562,8	1111	MHV-15(LS)BS-1111	62,99	2,480
3 x 30,7	2	MHV3-15(LS)BS-2	60,96	2,400

BOSTRIG MHV-15(LS)BS 8,7/15 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
3 x 46,0	1	MHV3-15(LS)BS-1	64,52	2,540
3 x 56,3	1/0	MHV3-15(LS)BS-1/0	67,82	2,670
3 x 66,5	2/0	MHV3-15(LS)BS-2/0	68,83	2,710
3 x 92,1	3/0	MHV3-15(LS)BS-3/0	77,47	3,050
3 x 112,6	4/0	MHV3-15(LS)BS-4/0	80,77	3,180
3 x 133,0	262	MHV3-15(LS)BS-262	83,57	3,290
3 x 158,6	313	MHV3-15(LS)BS-313	87,38	3,440
3 x 189,3	373	MHV3-15(LS)BS-373	91,44	3,600
3 x 225,1	444	MHV3-15(LS)BS-444	95,50	3,760
3 x 271,2	535	MHV3-15(LS)BS-535	101,09	3,980
3 x 327,5	646	MHV3-15(LS)BS-646	106,93	4,210
3 x 393,8	777	MHV3-15(LS)BS-777	113,54	4,470
3 x 562,8	1111	MHV3-15(LS)BS-1111	126,24	4,970
4 x 30,7	2	MHV4-15(LS)BS-2	68,07	2,680
4 x 46,0	1	MHV4-15(LS)BS-1	73,66	2,900
4 x 56,3	1/0	MHV4-15(LS)BS-1/0	77,22	3,040
4 x 66,5	2/0	MHV4-15(LS)BS-2/0	78,23	3,080
4 x 92,1	3/0	MHV4-15(LS)BS-3/0	86,61	3,410
4 x 112,6	4/0	MHV4-15(LS)BS-4/0	90,17	3,550
4 x 133,0	262	MHV4-15(LS)BS-262	93,47	3,680
4 x 158,6	313	MHV4-15(LS)BS-313	97,54	3,840
4 x 189,3	373	MHV4-15(LS)BS-373	102,36	4,030
4 x 225,1	444	MHV4-15(LS)BS-444	107,19	4,220
4 x 271,2	535	MHV4-15(LS)BS-535	113,03	4,450
4 x 327,5	646	MHV4-15(LS)BS-646	119,63	4,710
4 x 393,8	777	MHV4-15(LS)BS-777	127,00	5,000
4 x 562,8	1111	MHV4-15(LS)BS-1111	142,24	5,600

BOSTRIG MHV-15(LS)BS 12/20 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
1 x 30,7	2	MHV-15a(LS)BS-2	34,54	1,360
1 x 46,0	1	MHV-15a(LS)BS-1	36,07	1,420
1 x 56,3	1/0	MHV-15a(LS)BS-1/0	37,34	1,470
1 x 66,5	2/0	MHV-15a(LS)BS-2/0	37,85	1,490
1 x 92,1	3/0	MHV-15a(LS)BS-3/0	41,40	1,630
1 x 112,6	4/0	MHV-15a(LS)BS-4/0	42,67	1,680
1 x 133,0	262	MHV-15a(LS)BS-262	45,47	1,790
1 x 158,6	313	MHV-15a(LS)BS-313	47,50	1,870
1 x 189,3	373	MHV-15a(LS)BS-373	49,28	1,940
1 x 225,1	444	MHV-15a(LS)BS-444	52,07	2,050
1 x 271,2	535	MHV-15a(LS)BS-535	54,61	2,150
1 x 327,5	646	MHV-15a(LS)BS-646	57,40	2,260
1 x 393,8	777	MHV-15a(LS)BS-777	59,94	2,360
1 x 562,8	1111	MHV-15a(LS)BS-1111	65,53	2,580
3 x 30,7	2	MHV3-15a(LS)BS-2	66,04	2,600
3 x 46,0	1	MHV3-15a(LS)BS-1	69,85	2,750
3 x 56,3	1/0	MHV3-15a(LS)BS-1/0	74,42	2,930
3 x 66,5	2/0	MHV3-15a(LS)BS-2/0	75,44	2,970

BOSTRIG MHV-15(LS)BS 12/20 kV				
		DRAKA Cable Type Designation	Overall Diameter	Overall Diameter
mm ²	AWG/MCM		mm	Inches
3 x 92,1	3/0	MHV3-15a(LS)BS-3/0	82,80	3,260
3 x 112,6	4/0	MHV3-15a(LS)BS-4/0	85,85	3,380
3 x 133,0	262	MHV3-15a(LS)BS-262	88,39	3,480
3 x 158,6	313	MHV3-15a(LS)BS-313	92,71	3,650
3 x 189,3	373	MHV3-15a(LS)BS-373	96,77	3,810
3 x 225,1	444	MHV3-15a(LS)BS-444	100,84	3,970
3 x 271,2	535	MHV3-15a(LS)BS-535	106,17	4,180
3 x 327,5	646	MHV3-15a(LS)BS-646	113,54	4,470
3 x 393,8	777	MHV3-15a(LS)BS-777	118,62	4,670
3 x 562,8	1111	MHV3-15a(LS)BS-1111	131,83	5,190
4 x 30,7	2	MHV4-15a(LS)BS-2	74,93	2,950
4 x 46,0	1	MHV4-15a(LS)BS-1	79,50	3,130
4 x 56,3	1/0	MHV4-15a(LS)BS-1/0	82,80	3,260
4 x 66,5	2/0	MHV4-15a(LS)BS-2/0	84,07	3,310
4 x 92,1	3/0	MHV4-15a(LS)BS-3/0	92,20	3,630
4 x 112,6	4/0	MHV4-15a(LS)BS-4/0	95,50	3,760
4 x 133,0	262	MHV4-15a(LS)BS-262	98,81	3,890
4 x 158,6	313	MHV4-15a(LS)BS-313	103,63	4,080
4 x 189,3	373	MHV4-15a(LS)BS-373	107,95	4,250
4 x 225,1	444	MHV4-15a(LS)BS-444	112,52	4,430
4 x 271,2	535	MHV4-15a(LS)BS-535	118,62	4,670
4 x 327,5	646	MHV4-15a(LS)BS-646	126,75	4,990
4 x 393,8	777	MHV4-15a(LS)BS-777	132,59	5,220
4 x 562,8	1111	MHV4-15a(LS)BS-1111	147,32	5,800

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2020-01	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60092-354	2014-08	Electrical installations in ships - Part 354: Single- and three-core power cables with extruded solid insulation for rated voltages 6 kV (Um = 7,2 kV) up to 30 kV (Um = 36 kV)	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.

Job Id: **262.1-007168-12**
Certificate No: **TAE00003XZ**

Standard	Release	General description	Limitation
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2013-07 2013-09	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance ≥60%
IEC 60502-1	2009-11	power cables with extruded insulation and their accessories for rated voltages from 1 kv (um = 1,2 kv) up to 30 kv (um = 36 kv) - part 1: cables for rated voltages of 1 kv (um = 1,2 kv) and 3 kv (um = 3,6 kv)	
IEC 60502-2	2014-03	power cables with extruded insulation and their accessories for rated voltages from 1 kv (um = 1,2 kv) up to 30 kv (um = 36 kv) - part 2: cables for rated voltages from 6 kv (um = 7,2 kv) up to 30 kv (um = 36 kv)	
ICEA S93-639	2012-01	5-46kv shielded power cable for use in the transmission and distribution of electric energy	
UL 1072	2020-04	Medium-voltage power cable	

Marking of product

Draka 32- Type designation – Size – IEC 60332 Cat A – Voltage class.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE