

# TYPE APPROVAL CERTIFICATE

---

## This is to certify:

### That the Cable Ties

with type designation(s)

**KT4U046-yyy, KT6U046-yyy, KT4U078-yyy, KT6U078-yyy, KT4B046-yyy, KT6B046-yyy, KT4B078-yyy, KT6B078-yyy**

Issued to

**IDEX Technology(Suzhou)Co.,Ltd**  
**Suzhou, JIANGSU, China**

is found to comply with

**DNV rules for classification – Ships, offshore units, and high speed and light craft**

## Application :

---

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.**

**Material                      Metallic (Stainless steel)**

**Suitable for open deck    Yes**

Issued at **Hamburg** on **2021-09-27**

This Certificate is valid until **2026-09-26**.

for **DNV**

DNV local station: **Shanghai**

Approval Engineer: **Carsten Hunsalz**

---

**Arne Schaarmann**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.  
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

| Type:                      | KT4U046-yyy, KT6U046-yyy,KT4U078-yyy, KT6U078-yyy, KT4B046-yyy, KT6B046-yyy, KT4B078-yyy, KT6B078-yyy                                                          |            |                |                     |                           |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------|---------------------|---------------------------|
| Material:                  | Metallic Stainless steel 304ss Type KT4... 316ss Type KT6...<br><br>Type KT4B... and Type KT6B... Epoxy coated black<br>Type KT4U... and Type KT6U... Uncoated |            |                |                     |                           |
| Article                    | Length [mm]                                                                                                                                                    | Width [mm] | Thickness [mm] | Diameter Range [mm] | Loop Tensile Strength [N] |
| KT4U046-yyy<br>KT6U046-yyy | 150-1200                                                                                                                                                       | 4,5-4,7    | 0,25-0,28      | 12,7 to 369         | 845                       |
| KT4U078-yyy<br>KT6U078-yyy | 150-1500                                                                                                                                                       | 7,7-8,1    | 0,25-0,28      | 12,7 to 465         | 1245                      |
| KT4B046-yyy<br>KT6B046-yyy | 150-1200                                                                                                                                                       | 4,6-4,9    | 0,35-0,45      | 12,7 to 369         | 623                       |
| KT4B078-yyy<br>KT6B078-yyy | 150-1500                                                                                                                                                       | 7,8-8,2    | 0,35-0,45      | 12,7 to 465         | 712                       |

Details according manufacturer`s specification

Classification according to IEC 62275:

|                                |                                                                                                                                                                                           |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.1 Material:                  | Metallic                                                                                                                                                                                  |
| 6.2 Loop tensile strength:     | Type 2: Retains 100% strength after testing                                                                                                                                               |
| 6.3 Temperature:               | Maximum operation temperature [°C]: 300 / 150 coated types<br>Minimum operation temperature [°C]: -60 / -40 coated types<br>Minimum installation temperature [°C]: -60 / -40 coated types |
| 6.4 Contribution to fire:      | Non-flame propagating                                                                                                                                                                     |
| 6.5.1 Resistance to UV light:  | resistant                                                                                                                                                                                 |
| 6.5.2 Resistance to corrosion: | resistant                                                                                                                                                                                 |

## Application/Limitation

For fixing of cables, outdoor and indoor, onboard ships and mobile offshore units.

To be installed according with the manufacturer`s instructions and DNV rules.

## Type Approval documentation

Specification: IDEX Technology(Suzhou)Co.,Ltd,  
Drawing KT TAB, Data sheets--KT Tie Part List DNV 20210812, KT Tie Part List

Test Report: UL File E473020 dated 2021-04-06, 2021-03-10, 2019-06-27, 2020-07-27,  
ZODZ.E473020 dated 2021-05-20

## Tests carried out

Mandatory tests for metallic types according to type approval programme DNVGL-CP-0407 and IEC 62275:2018-08

Loop tensile strength for ties retaining 100% strength after testing.

## Marking of product

The smallest package is to be marked with the following:

- Manufacturer's name / trade mark & catalog type designation
- Manufacturer's rated load ( tensile strength ) as per catalogue
- Dimensions
- Type of product
- Maximum bundle diameter
- Temperature conditions

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE