



Certificate No:
TAE00004GV

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Flexible cable

with type designation(s)

0.6/1kV FX-RFOU(TC), 0.6/1(1.8/3)kV FX-RFOU(VFD)(TC), 1.8/3kV FX-RFOU(VFD)(TC)

Issued to

TMC Co., Ltd

Cheonan-si, Chungcheongnam-do, Korea, Republic of

is found to comply with

DNV rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Busan** on **2022-11-04**

This Certificate is valid until **2027-11-03**.

for **DNV**

DNV local station: **Seoul**

Approval Engineer: **Eun Jin Lee**

.....
Hanwee Low
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Type designation : 0.6/1kV FX-RFOU(TC), 0.6/1(1.8/3)kV FX-RFOU(VFD)(TC), 1.8/3kV FX-RFOU(VFD)(TC)

Conductor :	Stranded tinned annealed copper wires, Class 5
Insulation :	EPR
Inner covering :	Flame retardant halogen free thermoset compound
Armour :	Tinned annealed copper wire
	CU/PS tape for VFD type only
Sheath :	SHF2

No. of cores		Size (mm ²)
0.6/1kV	1C, 2C, 3C, 4C	1.5~300
	2C+E, 3C+E, 4C+E	1.5~240 + 1.5~120
	5C~44C	1.5, 1.5
0.6/1(1.8/3)kV 1.8/3kV	3C+E	10~240 +4~50

Declaration of properties (Circular)

Dynamic bending radius	Armoured : 8XD
Maximum speed	S bend : 0.3 m/s Reverse : 5 rpm
No. of bending cycles at +20°C	5,000
Suitable for torsion	Yes
Maximum torsion [Degrees/m]	±50 degrees/m
No. of cycles with maximum torsion at +20°C	10,000
Suitable for combined bending and torsion	No
Resistance to tensile load [kN]	20 N/mm ²

Application/Limitation

The requirements of SOLAS Chapter II-1 Part D Reg.45, 5.2 to limit Fire propagation along bunches of cables or wires are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
DNV-CP-0417	2021	DNV Class programme – Flexible electric cables	Declaration of properties
IEC 60092-350	2020	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-353	2016	Power cables for rated voltages 1kV and 3kV	
IEC 60092-360	2021	Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation, telecommunication cables	
IEC 60332-1	2015	Test for vertical flame propagation for a single insulated wire or cable - Apparatus	
IEC 60332-3-22	2018	Tests on electric and optical fibre cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Bunch test Category A
IEC 60754-1	2019	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen <0,5%
IEC 60754-2	2019	Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity	Halogen free ≥4,3pH, ≤10μS/mm
IEC 61034-1/2	2019	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke >60%

Standard	Release	General description	Limitation
IEC 60092-350 Annex E	2020	Cold bend test and impact test for low temperature behaviour	Cold bend: -40°C Cold impact: -35°C
NEK606	2016	Cables for offshore installations	Oil & Mud resistant – Category a/b/c/d

Marking of product

Voltage rating – FX-RFOU(TC) or FX-RFOU(VFD)(TC) – Size – IEC 60332-3 Cat.A – TMC – Year of manufacture – Length

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE