Certificate No:
TAE00004HK

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Electric Power Cable

with type designation(s)
FLAME-X 950 NKOGsekw 0,6/1 kV, FLAME-X 950 NKOGsekw EMC 0,6/1 kV

Issued to
Tele-Fonika Kable S.A.
Myslenice, **Poland**

is found to comply with
DNV rules for classification – Ships, offshore units, and high speed and light craft

Application :

General power, lighting and control, Fire resistant
Products approved by this certificate are accepted for installation on all vessels classed by DNV.

Type	Rated voltage (kV)	Temp. class (°C)
FLAME-X 950 NKOGsekw 0,6/1 kV	0,6/1	90
FLAME-X 950 NKOGsekw EMC 0,6/1 kV	0,6/1	90

Issued at **Høvik** on **2022-10-08**
This Certificate is valid until **2027-10-07**.
DNV local station: **Katowice CMC**

Approval Engineer: **Ivar Bull**

for **DNV**

Frederik Tore Elter
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

FLAME-X 950 NKOGsekw 0,6/1 kV or FLAME-X 950 NKOGsekw EMC 0,6/1 kV

Construction:

Conductors:	Plain stranded copper class 2
Core insulation:	Ceramic HF S95
Inner covering:	Halogen free compound or Tape for multicore cables over 25mm^2
Metal covering:	NKOGsekw Plain copper wire braid NKOGsekw EMC: Cu/PE tape (coverage 100%) & copper wire braid
Outer sheath:	SHF1

No of cores:	Cross sectional area [mm^2]
1	1 - 300
2	1 – 50
3	1 - 240
4	1 - 185
5	1 - 70
9, 14	1,5
7, 10, 12, 16, 19, 20, 24, 27, 30, 37	1,0 1,5 2,5

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publication 60331.

The requirements of SOLAS Amendments 1981 Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

	Release	General description	Limitation
DNV-CP-0399	2021-08	Class Programme Electric cables	
IEC 60092-350	2020-01	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2021-01	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	Including: Ozone resistance
IEC 60092-353	2016-09	Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV	
IEC 60331-1/2	2018-03	Fire resistance / Circuit integrity – Test for method for fire with shock at temperature of at least 830ºC for cables rated up to and including 0,6/1 kV	120 min
IEC 60331-21	1999-04	Tests for electric cables under fire conditions – Circuit integrity – Part 21: Procedures and requirements – Cables of rated voltage up to and including 0,6/1,0 kV	Minimum 90 min. flame application + 15 min. cooling period.
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
IEC 60754-1	2019-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen

	Release	General description	Limitation
IEC 60754-2	2019-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2019-11	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance ≥60%
EN 50200	2006-06	Method of test for resistance to fire of unprotected small cables for use in emergency circuits	

Marking of product

TF Kable 1 or TFK 1 – FLAME-X 950 NKOGsekw or FLAME-X 950 NKOGsekw EMC – size – 0,6/1 kV –
IEC 60331 - IEC 60332-3-22

TF Kable 1 or TFK 1 = Myslenice factory

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years.
A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE